Eaton 5S 1000i Unterbrechungsfreie Stromversorgung (USV) 1 kVA 600 W 8 AC-Ausgänge





Marke : Eaton

Artikel-Code: 5S1000I

Produktname : 5S 1000i

5S 1000i

Eaton 5S 1000i Unterbrechungsfreie Stromversorgung (USV) 1 kVA 600 W 8 AC-Ausgänge:

Die USV Eaton 5S bietet ein kosteneffizientes Line-Interactive-Batterie-Backup mit Spannungsregelung für kleine und mittlere Unternehmen mit Workstations, Desktop-PCs, Telefonanlagen und POS-Anwendungen. Mit ihren kompakten Abmessungen kann die USV 5S als eigenständiger Tower oder unter einem Computer-Monitor aufgestellt werden.
Eaton 5S 1000i. Ausgangskapazität: 1 kVA, Ausgangsleistung: 600 W, Eingangs-Betriebsspannung (min): 175 V. AC-Steckertypen: C13-Koppler, Stecker: C14-Koppler, Anzahl der AC-Ausgänge: 8 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Typische Backup-Zeit bei halber Belastung: 14 min. Formfaktor: Tower, Produktfarbe: Schwarz. Sicherheit: IEC/EN 62040-1, IEC/EN 62040 -2, CB, CE

Merkmale	
Ausgangskapazität *	1 kVA
Ausgangsleistung *	600 W
Eingangs-Betriebsspannung (min) *	175 V
Eingangs-Betriebsspannung (max) *	275 V
Eingangsfrequenz *	50/60 Hz
Ausgangs-Betriebsspannung (min)	230 V
Ausgangs-Betriebsspannung (max)	230 V
Geräuschpegel	40 dB
Druckanstiegsschutz	✔
Überspannungsschutz-Funktionen	Faxen, Modem, Netzwerk, Telefon

Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler
Stecker	C14-Koppler
Anzahl der AC-Ausgänge	8 AC-Ausgänge
Anzahl USB 2.0 Anschlüsse	1
Modem (RJ-11) Port	1

Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Typische Backup-Zeit bei halber Belastung	14 min
Automatischer Batterietest	✔
Kaltstart	✔

Design	
Formfaktor *	Tower
Produktfarbe *	Schwarz
LED-Anzeigen	✔

Safety regulation & standards	
Sicherheit	IEC/EN 62040-1, IEC/EN 62040 -2, CB, CE

Gewicht und Abmessungen	
Breite	87 mm
Tiefe	382 mm
Höhe	250 mm
Gewicht	9,48 kg

Logistikdaten	
Warentarifnummer (HS)	85078000

0743172436962

743172436962

5054444003894

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 16-NOV-2026. Prints or copies of Information are only valid on the printed Publication date