CyberPower PDU24005, Rackmount 1U, ATS PDU, Metered, ATS Eingang (2)230V/16A IEC-320 C20, Ausgang IEC-320 C19 (2) + IEC-320 C13 (8)



Marke : CyberPower

Artikel-Code: PDU24005

Produktname : PDU24005, Rackmount 1U, ATS PDU, Metered, ATS Eingang (2)230V/16A IEC-320 C20, Ausgang IEC-320 C19 (2) + IEC-320 C13 (8)

- Lokales Echtzeit-Monitoring
- Schnelle Umschaltzeit (max□10 ms)
- Digitale Echtzeit-Lastanzeige
- Hot-Swap tauschbares LCD
- Firmware-Upgrade über USB
- Flexible Montage am Rack
- IEC-Steckdose
- Doppelter Eingang
- Metallgehäuse in industrieller Qualität
- Benutzer konfigurierbares Farb-LCD
- LED-Statusanzeige
- Vom Benutzer aktualisierbare Firmware
- Kabelhalterung



PDU Stromverteiler
CyberPower PDU24005, Rackmount 1U, ATS PDU, Metered, ATS Eingang (2)230V/16A IEC-320 C20, Ausgang IEC-320 C19 (2) + IEC-320 C13 (8). PDU-Typen: Messgerät, Rack-Kapazität: 1U, Typ: Einphasig. Anzahl der AC-Ausgänge: 10 AC-Ausgänge, AC-Steckertypen: C13-Koppler, C19-Koppler, Stecker: C20-Koppler. LED-Anzeigen: Link, Status, Kabellänge: 3,05 m. Nominale Eingang Spannung: 200 - 240 V, Stromstärke (maximal): 12 A, AC Eingangsfrequenz: 50 / 60 Hz. Konformitätsbescheinigungen: CB, CE, Eidgenössische Kommunikationskommission (FCC), RoHS, UL, Zertifizierung: FCC Class A, UL62368, EN 55032 Class A, IEC 62368

Design	
PDU-Typen *	Messgerät
Typ	Einphasig
Rack-Kapazität *	1U
Montage	Horizontal
Gehäusematerial	Stahl
Produktfarbe	Schwarz
Display	LCD

Anschlüsse und Schnittstellen	
Anzahl der AC-Ausgänge *	10 AC-Ausgänge
Stecker	C20-Koppler
AC-Steckertypen *	C13-Koppler, C19-Koppler
Anzahl serielle Anschlüsse	1
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1
Anzahl der USB-Anschlüsse	1

Merkmale	
LED-Anzeigen	Link, Status
Kabellänge	3,05 m

Management-Funktionen	
Upgradefähige Firmware	✔

Energie	
Nominale Eingang Spannung *	200 - 240 V
AC Eingangsfrequenz	50 / 60 Hz
Stromstärke (maximal) *	12 A
Nominale Ausgang Spannung	200 - 240 V
Energieschutzeigenschaften	Überlastschutz

Zertifikate	
Zertifizierung	FCC Class A, UL62368, EN 55032 Class A, IEC 62368

Nachhaltigkeit	
Nachhaltigkeitskonformität	✔

Betriebsbedingungen	
Betriebstemperatur	0 - 45 °C
Temperaturbereich bei Lagerung	-15 - 95 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 4000 m
Höhe bei Lagerung	0 - 15000 m
Temperatur Betriebsumgebung	32 - 113 °F

Gewicht und Abmessungen	
Breite	433 mm
Tiefe	215 mm
Höhe	44 mm
Gewicht	3,2 kg

Lieferumfang	
Verpackungsinhalt	PDU24005, Benutzerhandbuch, Kabelauffangbehälter, Montagehalterungen, Kabelbinder, Schraubensatz, Kaltgeräteverlängerung, Serielles Kabel

Verpackungsdaten	
Paketgewicht	6 kg
Verpackungsbreite	550 mm

Energie	
Schutzschalter	✔

Zertifikate	
Konformitätsbescheinigungen	CB, CE, Eidgenössische Kommunikationskommission (FCC), RoHS, UL

Verpackungsdaten	
Verpackungstiefe	398 mm
Verpackungshöhe	125 mm

Logistikdaten	
Garantiezeit	2 Jahr(e)

4711027799797

0649532933358

649532933358

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-JUN-2026. Prints or copies of Information are only valid on the printed Publication date