




TP-Link EAP215-BRIDGE KIT(EU) WLAN Access Point 867 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Artikel-Code: EAP215-BRIDGE KIT(EU)

Produktname : EAP215-BRIDGE KIT(EU)

TP-Link EAP215-BRIDGE KIT(EU). 5 GHz, Maximale Datenübertragungsrate: 867 Mbit/s. Unterstützte Sicherheitsalgorithmen: SNMP, SNMPv2, SNMPv3, SSH. Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß



Merkmale		Energie	
2,4 GHz *	✗	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Power-over-Ethernet (PoE)-Typ unterstützt	Passive PoE
6 GHz *	✗	DC Spannungsrange	12 V
Maximale Datenübertragungsrate *	867 Mbit/s	Design	
Maximale Datenübertragungsrate (5 GHz)	867 Mbit/s	Platzierung *	Stange
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Produktfarbe *	Weiß
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n	Reset-Knopf	✓
		LED-Anzeigen	✓
Verkabelungstechnologie	10/100/1000Base-T(X)	Antenne	
MIMO	✓	Antennentyp *	Intern
MIMO-Typ	Multi User MIMO	Antennenrichtungsart	Direktional
VLAN-Unterstützung	✓	Antennenfunktionen	Integrierte Antenne
Ratenbeschränkung	✓	Antenne Zunahmenniveau (max)	11 dBi
Quality of Service (QoS) Support	✓	Polarisation	Duale Polarisation
BeamForming	✓	Zertifikate	
Sendeleistung (CE)	<23dBm (5 GHz, band 1/2, EIRP); <30dBm (5 GHz band3, EIRP)	Zertifizierung	CE, FCC, RoHS
Sendeleistung (FCC)	<22dBm (5 GHz band1/4)	Gewicht und Abmessungen	
Sicherheit		Breite	224 mm
Unterstützte Sicherheitsalgorithmen *	SNMP, SNMPv2, SNMPv3, SSH	Tiefe	79 mm
MAC Adressen Filtern	✓	Höhe	60 mm
Fernauthentifizierungs-Einwahl-Benutzerdienst (RADIUS)	✓	Gewicht	330,9 g
Zugriffskontrollliste	✓	Lieferumfang	
Management-Funktionen		Schnellstartübersicht	✓
Web-basiertes Management	✓	Betriebsbedingungen	
		Relative Luftfeuchtigkeit in Betrieb	10 - 90%

Management-Funktionen		Betriebsbedingungen	
Syslog	✓	Betriebstemperatur	-40 - 70 °C
Anschlüsse und Schnittstellen		Temperaturbereich bei Lagerung	-40 - 70 °C
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	3	Luftfeuchtigkeit bei Lagerung	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.