



TP-Link Omada ES205GP(UN) Netzwerk-Switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz



Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: ES205GP(UN)

Produktname : ES205GP(UN)

TP-Link Omada ES205GP(UN). Switch-Typ: Managed. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 5. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 10 Gbit/s. Netzstandard: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3at, IEEE 802.3x. DC input Spannung: 53.5 V. Power over Ethernet (PoE). Wandmontage

Management-Funktionen		Design	
Switch-Typ *	Managed	Reset-Knopf	✓
Quality of Service (QoS) Support	✓	LED-Anzeigen	✓
Cloud-verwaltet	✓	Wandmontage	✓
Anschlüsse und Schnittstellen		Leistungen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	5	Ventilatorlos	✓
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Energie	
Netzwerk		Energiequelle *	AC/DC
Netzstandard *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3at, IEEE 802.3x	Netzteil enthalten *	✓
10G-Unterstützung *	✗	DC input Spannung	53.5 V
Port-Spiegelung	✓	Power over Ethernet (PoE)	
Unterstützung Datenflusssteuerung	✓	Power over Ethernet (PoE) *	✓
Link Aggregation	✓	Anzahl Power over Ethernet (PoE) Anschlüsse	4
Auto MDI/MDI-X	✓	Anzahl Power over Ethernet plus (PoE+) Anschlüsse	4
Auto-Negotiation-Funktion	✓	Power over Ethernet (PoE) Leistung pro Anschluss	30 W
VLAN-Unterstützung	✓	Gesamtleistung Power over Ethernet (PoE)	65 W
Virtuelle LAN-Funktionen	MTU VLAN, Port-based VLAN, Tagged VLAN	Betriebsbedingungen	
Lichtwellenleiter		Betriebstemperatur	0 - 40 °C
Transmissionsentfernung (max)	0,25 km	Temperaturbereich bei Lagerung	-40 - 70 °C
Datenübertragung		Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Routing-/Switching-Kapazität *	10 Gbit/s	Luftfeuchtigkeit bei Lagerung	5 - 90%
Transferrate	7,4 Mpps	Gewicht und Abmessungen	
MAC-Adressentabelle *	8000 Eintragungen	Breite	100 mm
Store-and-Forward	✓	Tiefe	98 mm
Jumbo Frames Unterstützung	✓	Höhe	25 mm
Jumbo-Frames	15	Lieferumfang	
Datenpaket-Pufferspeicher	4 MB	Benutzerhandbuch	✓
Sicherheit		Verpackungsdaten	
DHCP-Funktionen	DHCP client	Verpackungsart	Box
IGMP-Snooping	✓	Zertifikate	
Loop Protection	✓	Konformitätsbescheinigungen	CE, Eidgenössische Kommunikationskommission (FCC), RoHS

Design

Produktfarbe Schwarz

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.