




LevelOne IES-0600 Netzwerk-Switch Gigabit Ethernet (10/100/1000) Schwarz

Marke : LevelOne

Artikel-Code: IES-0600

Produktname : IES-0600

LevelOne IES-0600. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 4. Vollduplex. MAC-Adressentabelle: 1024 Eintragungen, Routing-/Switching-Kapazität: 12 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Wandmontage



Anschlüsse und Schnittstellen		Energie	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	4	Energieschutzeigenschaften	Überlastschutz, Umgekehrte Polarität
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
Menge SFP-Modul-Steckplätze	1	Power over Ethernet (PoE) *	✗
Netzwerk		Sonstige Funktionen	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Terminalblock-Anschluss	✓
10G-Unterstützung *	✗	Betriebsbedingungen	
Vollduplex	✓	Betriebstemperatur	-40 - 75 °C
Unterstützung Datenflusssteuerung	✓	Temperaturbereich bei Lagerung	-40 - 85 °C
Auto MDI/MDI-X	✓	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Auto-Negotiation-Funktion	✓	Luftfeuchtigkeit bei Lagerung	5 - 95%
Datenübertragung		Gewicht und Abmessungen	
Routing-/Switching-Kapazität *	12 Gbit/s	Breite	40 mm
MAC-Adressentabelle *	1024 Eintragungen	Tiefe	105 mm
Store-and-Forward	✓	Höhe	38 mm
Jumbo-Frames	10000	Gewicht	720 g
Paketweiterleitungsrate (1 Gbit/s)	1488000 pps	Lieferumfang	
Paketweiterleitungsrate (100 Mbit/s)	148000 pps	Schnellstartübersicht	✓
Paketweiterleitungsrate (10 Mbit/s)	14880 pps	Verpackungsdaten	
Datenpaket-Pufferspeicher	1 MB	Verpackungsart	Box
Design		Verpackungsbreite	215 mm
Produktfarbe	Schwarz	Verpackungstiefe	165 mm
Gehäusematerial	Metall	Verpackungshöhe	65 mm
LED-Anzeigen	Aktivität, Link, Leistung	Paketgewicht	120 g
Internationale Schutzart (IP-Code)	IP30	Zertifikate	
Wandmontage	✓	Zertifizierung	FCC Part 15 Subpart B Class A CE
DIN-Schienen-Montage	✓		EN 55022 Class A EN61000-4-2 (ESD) Level 3 EN61000-4-3 (RS) Level 3 EN61000-4-4 (EFT) Level 3 EN61000-4-5 (Surge) Level 3 EN61000-4-6 (CS) Level 3 EN61000-4-8 (Magnetic Field) Level 3 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6 UL 508
Energie			
Eingangsspannung	5 - 56 V		

Logistikdaten

Ursprungsland	Taiwan
Warentarifnummer (HS)	85176990



4015867188491



4015867224250

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.