



## LevelOne 48V DC Industrie-Netzteil, 75W, DIN-Schiene,-20 ~ +70 °C



**Marke :** LevelOne

**Artikel-Code:** POW-4822

**Produktname :** 48V DC Industrie-Netzteil, 75W, DIN-Schiene,-20 ~ +70 °C

- Universeller AC-Eingang im gesamten Bereich
- Kurzschluss-, Überlast- und Überspannungsschutz
- Lüfterloses Design unterstützt
- DIN-Schieneninstallation
- 100% Volllast

- Burn-in-Test mit DC OK Relaiskontakt4

48V DC Industrie-Netzteil, 75W, DIN-Schiene,-20 ~ +70 °C

LevelOne 48V DC Industrie-Netzteil, 75W, DIN-Schiene,-20 ~ +70 °C. Gesamtleistung: 75 W, AC

Eingangsspannung: 90 -264 V, Spitzenstrom: 76,8 W. Mittlere Betriebsdauer zwischen Ausfällen (MTBF):

486200 h. Produktfarbe: Blau, Silber. Sicherheit: EN 55032 (CISPR32) Class A EN

61000-3-2,-3,EACTPTC020,CNS13438 Class A EN 61000-4-2,3,4,5,6,8,11.... Breite: 32 mm, Tiefe: 102

mm, Höhe: 125,2 mm

| Energie                                          |                                                                                                                                                | Gewicht und Abmessungen    |             |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-------------|
| Gesamtleistung *                                 | 75 W                                                                                                                                           | Tiefe                      | 102 mm      |
| Spitzenstrom                                     | 76,8 W                                                                                                                                         | Höhe                       | 125,2 mm    |
| AC Eingangsspannung *                            | 90 -264 V                                                                                                                                      | Gewicht                    | 430 g       |
| AC Eingangsfrequenz                              | 47 - 63 Hz                                                                                                                                     | Verpackungsdaten           |             |
| Eingangsstrom                                    | 1.45 A                                                                                                                                         | Verpackungsbreite          | 53 mm       |
| Haltezeit                                        | 16 ms                                                                                                                                          | Verpackungstiefe           | 132 mm      |
| Energieschutzeigenschaften                       | Überlastschutz, Überspannung, Kurzschluß                                                                                                       | Verpackungshöhe            | 147 mm      |
| Leistungen                                       |                                                                                                                                                | Paketgewicht               | 500 g       |
| Mittlere Betriebsdauer zwischen Ausfällen (MTBF) | 486200 h                                                                                                                                       | Verpackungsart             | Box         |
| Design                                           |                                                                                                                                                | Logistikdaten              |             |
| Produktfarbe                                     | Blau, Silber                                                                                                                                   | Anzahl Kartons pro Palette | 20 Stück(e) |
| Betriebsbedingungen                              |                                                                                                                                                | Breite des Versandkartons  | 282 mm      |
| Betriebstemperatur                               | -20 - 70 °C                                                                                                                                    | Länge des Versandkartons   | 313 mm      |
| Relative Luftfeuchtigkeit in Betrieb             | 0 - 90%                                                                                                                                        | Höhe des Versandkartons    | 393 mm      |
| Safety regulation & standards                    |                                                                                                                                                | Gewicht Versandkarton      | 16,8 kg     |
| Sicherheit                                       | EN 55032 (CISPR32) Class A EN 61000-3-2,-3,EACTPTC020,CNS13438 Class A EN 61000-4-2,3,4,5,6,8,11 EN 61204-3 EN 55035 EN 61000-6-2 (EN 50082-2) | Warentarifnummer (HS)      | 8504403090  |
| Gewicht und Abmessungen                          |                                                                                                                                                | Ursprungsland              | China       |
| Breite                                           | 32 mm                                                                                                                                          | Sonstige Funktionen        |             |
|                                                  |                                                                                                                                                | Spannungstoleranz          | 1%          |
|                                                  |                                                                                                                                                | Ausgang Spannung (Note)    | 48V         |



4015867236598

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.