



APC Smart-UPS Li-ion SMTL2200RM12UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA



Marke : APC

Artikel-Code: SMTL2200RM12UC

Produktname : APC Smart-UPS Li-ion SMTL2200RM12UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA



APC Smart-UPS Li-ion SMTL2200RM12UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA
APC Smart-UPS Li-ion SMTL2200RM12UC - 8xC13 & 1xC19, Rackmount 2U, SmartConnect, 2200VA. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 2,2 kVA, Ausgangsleistung: 1980 W. AC-Steckertypen: C13-Koppler, C19-Koppler, Anzahl der AC-Ausgänge: 10 AC-Ausgänge, Serielle Schnittstelle: RJ-45. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Batteriebensdauer (max.): 5 Jahr(e), Akkuladezeit: 3 h. Formfaktor: Rackmount/Tower, Produktfarbe: Schwarz, Grau, Rack-Kapazität: 2U. Konformitätsbescheinigungen: CE, GS mark, RoHS, VDE, Zertifizierung: IRAM, RCM

Merkmale		Akku/Batterie	
USV-Topologie *	Line-Interaktiv	Hot-Swap-Batterie	✓
Ausgangskapazität *	2,2 kVA	Automatischer Batterietest	✓
Ausgangsleistung *	1980 W	Kaltstart	✓
Wellenform *	Sine	Design	
Eingangs-Betriebsspannung (min) *	151 V	Formfaktor *	Rackmount/Tower
Eingangs-Betriebsspannung (max) *	302 V	Rack-Kapazität	2U
Eingangsfrequenz *	50/60 Hz	Kabellänge	2 m
Ausgangs-Betriebsspannung (min)	220 V	Produktfarbe *	Schwarz, Grau
Ausgangs-Betriebsspannung (max)	240 V	Display-Typ	LCD
Output Frequenz	50/60 Hz	LED-Anzeigen	✓
Automatische Spannungsregulierung	✓	Betriebsbedingungen	
Anstieg der Energiemenge	375 J	Betriebstemperatur	0 - 40 °C
Reaktionszeit	6 ms	Temperaturbereich bei Lagerung	-15 - 45 °C
Wärmeableitung	215 BTU/h	Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Anzahl der Eingangs-Phasen	1	Luftfeuchtigkeit bei Lagerung	0 - 95%
Anzahl der Ausgangs-Phasen	1	Höhe bei Betrieb	0 - 3048 m
Ausgangsspannung	5%	Höhe bei Lagerung	0 - 15240 m
Gesamtverzerrungsfaktor THD	55 dB	Zertifikate	
Geräuschpegel	✓	Konformitätsbescheinigungen	CE, GS mark, RoHS, VDE
Akustische Signale	✓	Zertifizierung	IRAM, RCM
Auto-Neustart	✓	Lieferumfang	
Energiequelle	AC	Rackmontageset	✓
Anschlüsse und Schnittstellen		Mitgelieferte Kabel	USB-Kabel
AC-Steckertypen	C13-Koppler, C19-Koppler	Management-Karte enthalten	✗
Anzahl der AC-Ausgänge	10 AC-Ausgänge	Nachhaltigkeit	
Anzahl der Output IEC Jumper	3	Nachhaltigkeitskonformität	✓
USB Anschluss	✓	Gewicht und Abmessungen	
Serielle Schnittstelle	✓	Breite	432 mm
Serielle Schnittstelle	RJ-45	Tiefe	683 mm
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1	Höhe	86 mm
SmartSlot	✓	Gewicht	42,3 kg
SmartConnect-Anschluss	✓		

Akku/Batterie		Verpackungsdaten	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)	Verpackungsbreite	980 mm
Batterielebensdauer (max.)	5 Jahr(e)	Verpackungstiefe	600 mm
Akkuladezeit	3 h	Verpackungshöhe	254 mm
		Paketgewicht	49,7 kg
Sonstige Funktionen			
Eingang Verbindungstyp		BS1363A British, IEC 320 C20, Schuko CEE 7 / EU1-16P	
Nominale Ausgang Spannung		230 V	
Nominale Eingang Spannung		230 V	



0731304643197



731304643197

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.