

TP-Link EAP610 V1 1201 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Artikel-Code: EAP610(EU)

Produktname : EAP610 V1

TP-Link EAP610 V1. 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 1201 Mbit/s. Unterstützte Sicherheitsalgorithmen: 802.1x RADIUS, HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA2-Enterprise, WPA3-Enterprise. Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß



Merkmale		Protokolle	
2,4 GHz *	✓	Universal Plug and Play (UPnP)	✓
5 GHz *	✓	Anschlüsse und Schnittstellen	
6 GHz *	✗	Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Maximale Datenübertragungsrate *	1201 Mbit/s	Energie	
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s	Power over Ethernet (PoE) *	✓
Maximale Datenübertragungsrate (5 GHz)	1201 Mbit/s	AC Eingangsspannung	12 V
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Stromverbrauch (Standardbetrieb)	12,8 W
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at	Design	
Verkabelungstechnologie	10/100/1000Base-T(X)	Platzierung *	Zimmerdecke, Wand
Automatische Kanalwahl	✓	Produktfarbe *	Weiß
MIMO	✓	Reset-Knopf	✓
MIMO-Typ	Multi User MIMO	LED-Anzeigen	✓
Spread-Spectrum Methode	OFDMA	Antenne	
VLAN-Unterstützung	✓	Antennentyp *	Intern
Virtuelle LAN-Funktionen	VLAN mapping	Antennenrichtungsart	Mit kugelförmiger Richtcharakteristik
Ratenbeschränkung	✓	Anzahl der Antennen	4
Kabellose Isolierung	✓	Zertifikate	
Bandsteuerung	✓	Konformitätsbescheinigungen	CE, RoHS
Airtime Fairness (ATF)	✓	Zertifizierung	CE, FCC, RoHS
Quality of Service (QoS) Support	✓	Gewicht und Abmessungen	
BeamForming	✓	Breite	243 mm
Sendeleistung (CE)	20 - 23 dbm	Tiefe	243 mm
Sendeleistung (FCC)	25 - 25 dbm	Höhe	64 mm

Sicherheit		Lieferumfang	
Unterstützte Sicherheitsalgorithmen *	802.1x RADIUS, HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA2-Enterprise, WPA3-Enterprise	Menge pro Packung	1 Stück(e)
MAC Adressen Filtern	✓	AC-Netzadapter	✓
Funktionen Service Set Identifier (SSID)	Multiple SSIDs	Montageset	✓
Anzahl der SSID-Unterstützung	16	Schnellstartübersicht	✓
Zugriffkontrollliste	✓	Betriebsbedingungen	
		Relative Luftfeuchtigkeit in Betrieb	0 - 40%
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.