



TP-Link FESTA F65-OUTDOOR(EU) WLAN Access Point 3000 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Artikel-Code: FESTA F65-OUTDOOR(EU)

Produktname : FESTA F65-OUTDOOR(EU)

TP-Link FESTA F65-OUTDOOR(EU). 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 3000 Mbit/s.
Unterstützte Sicherheitsalgorithmen: WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal. Power over Ethernet (PoE). Produktfarbe: Weiß



Merkmale		Energie	
2,4 GHz *	✓	DC Spannungsrange	12 V
5 GHz *	✓	Eingangsstrom	1.2 A
6 GHz *	✗	Design	
Maximale Datenübertragungsrate *	3000 Mbit/s	Platzierung *	Wand
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s	Produktfarbe *	Weiß
Maximale Datenübertragungsrate (5 GHz)	2402 Mbit/s	Internationale Schutzart (IP-Code)	IP67
		Reset-Knopf	✓
		Antenne	
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at	Antennentyp *	Intern
Zahl der Benutzer	250 Benutzer	Antennenrichtungsart	Mit kugelförmiger Richtcharakteristik
MIMO	✓	Anzahl der Antennen	2
MIMO-Typ	Multi User MIMO	Antenne Zunahmehöhe (max)	5 dBi
Spread-Spectrum Methode	OFDMA	Zertifikate	
VLAN-Unterstützung	✓	Konformitätsbescheinigungen	
Quality of Service (QoS) Support	✓	CE, Eidgenössische Kommunikationskommission (FCC), Industry Canada (IC), RoHS	
Sicherheit		Gewicht und Abmessungen	
Unterstützte Sicherheitsalgorithmen *	WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal	Breite	280,4 mm
MAC Adressen Filtern	✓	Tiefe	160,5 mm
Funktionen Service Set Identifier (SSID)	Multiple SSIDs, SSID broadcast	Höhe	63,5 mm
Anzahl der SSID-Unterstützung	16	Gewicht	780 g
Management-Funktionen		Lieferumfang	
Web-basiertes Management	✓	AC-Netzadapter	✓
		PoE-Adapter enthalten (Power over Ethernet)	✓
		Montageset	✓

Anschlüsse und Schnittstellen		Lieferumfang	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1	Schnellstartübersicht	✓
Gleichstrom-Anschluss (DC)	✓	Betriebsbedingungen	
Energie		Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Power over Ethernet (PoE) *	✓	Betriebstemperatur	-30 - 70 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.