



TP-Link Omada EAP650-OUTDOOR(EU) WLAN Access Point 3000 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: EAP650-OUTDOOR(EU)

Produktname : EAP650-OUTDOOR(EU)

TP-Link Omada EAP650-OUTDOOR(EU). 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 3000 Mbit/s. Unterstützte Sicherheitsalgorithmen: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise. Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß



Merkmale		Anschlüsse und Schnittstellen	
2,4 GHz *	✓	Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
5 GHz *	✓	Energie	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximale Datenübertragungsrate *	3000 Mbit/s	Design	
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s	Platzierung *	Stange, Wand
Maximale Datenübertragungsrate (5 GHz)	2402 Mbit/s	Produktfarbe *	Weiß
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Internationale Schutzart (IP-Code)	IP67
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at	Reset-Knopf	✓
		LED-Anzeigen	✓
Verkabelungstechnologie	10/100/1000Base-T(X)	Antenne	
Zahl der Benutzer	250 Benutzer	Antennentyp *	Intern
Automatische Kanalwahl	✓	Antennenrichtungsart	Mit kugelförmiger Richtcharakteristik
Automatischer Kanalscan	✓	Zertifikate	
MIMO	✓	Zertifizierung	CE, FCC, RoHS
MIMO-Typ	Multi User MIMO	Gewicht und Abmessungen	
AP-Modus-Eigenschaften anpassen	Vernetzung von Netzen	Breite	280,4 mm
VLAN-Unterstützung	✓	Tiefe	106,5 mm
Ratenbeschränkung	✓	Höhe	56,8 mm
Bandsteuerung	✓	Lieferumfang	
Airtime Fairness (ATF)	✓	Menge pro Packung	1 Stück(e)
Quality of Service (QoS) Support	✓	Montageset	✓
BeamForming	✓	Schnellstartübersicht	✓

Sicherheit		Betriebsbedingungen	
Unterstützte Sicherheitsalgorithmen *	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
MAC Adressen Filtern	✓	Betriebstemperatur	-30 - 70 °C
Funktionen Service Set Identifier (SSID)	Multiple SSIDs, SSID-Übertragung ein/aus	Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.