

NETGEAR GS316PP Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz



Marke : NETGEAR

Artikel-Code: GS316PP-100EUS

Produktname : GS316PP Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz



GS316PP - 16-Port GB PoE+ unmanaged Switch 183W FlexPoE

NETGEAR GS316PP Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz:

NETGEAR SOHO Ethernet Unmanaged Switches

Die SOHO Ethernet Unmanaged Switches ermöglichen benutzerfreundliche und preisgünstige Netzwerkkonnektivität zu Hause sowie in kleinen Büros oder Heimbüros. Sie sind benutzerfreundlich, zuverlässig und verfügen über ein Metallgehäuse. Die Power-Over-Ethernet (PoE)-Unterstützung umfasst sowohl die Stromversorgung als auch die Datenübertragung über ein einziges CAT-5-Netzwerkkabel für Geräte wie IP-Sicherheitskameras, VoIP-Telefone, Wireless Access Points und viele mehr. Mit diesen Plug-and-Play-Switches können Sie Ihre Geräte ohne Konfigurationsaufwand in Ihr Netzwerk einbinden. Die Switches sind in 5- bzw. 48-Port-Konfigurationen erhältlich und unterstützen außerdem Energiespartechnologien, mit denen Sie Strom und Geld sparen können.

Management-Funktionen		Design	
Switch-Typ *	Unmanaged	LED-Anzeigen	Aktivität, Link, PoE, Leistung, Geschwindigkeit
Quality of Service (QoS) Support	✓	Wandmontage	✓
Anschlüsse und Schnittstellen		Leistungen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	16	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	2362192 h
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Energie	
Netzstecker	DC-Anschluss	DC input Spannung	54 V
Netzwerk		Eingangsstrom	3.7 A
Netzstandard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Stromverbrauch (max.)	195,9 W
10G-Unterstützung *	✗	Power over Ethernet (PoE)	
Vollduplex	✓	Power over Ethernet (PoE) *	✓
Unterstützung Datenflusssteuerung	✓	Anzahl Power over Ethernet plus (PoE+) Anschlüsse	16
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) Leistung pro Anschluss	30 W
Auto-Abtastung	✓	Gesamtleistung Power over Ethernet (PoE)	183 W
Auto-Negotiation-Funktion	✓	Betriebsbedingungen	
Datenübertragung		Betriebstemperatur	0 - 40 °C
Routing-/Switching-Kapazität *	32 Gbit/s	Temperaturbereich bei Lagerung	-20 - 70 °C
MAC-Adressentabelle *	4000 Eintragungen	Relative Luftfeuchtigkeit in Betrieb	0 - 90%
Wartezeit (1 Gbps)	3,7 µs	Höhe bei Betrieb	0 - 3000 m
Jumbo Frames Unterstützung	✓	Wärmeableitung	669,9 BTU/h
Jumbo-Frames	9216	Gewicht und Abmessungen	
Paketweiterleitungsrate (1 Gbit/s)	1448000 pps	Breite	286 mm
Datenpaket-Pufferspeicher	1 MB	Tiefe	102 mm
Sicherheit		Höhe	27 mm
Warteschleifenplanungs-Algorithmen	Weighted Round Robin (WRR)	Gewicht	880 g
Design		Zertifikate	
Rack-Einbau *	✗	Zertifizierung	CE, FCC Part A, IC A, RCM, VCCI, BSMI, KC, CB, CE LVD
Produktfarbe	Schwarz	Logistikdaten	
Gehäusematerial	Metall	Warentarifnummer (HS)	85176990



0606449146912



606449146912

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.