

ASUS RS720A-E13-RS24G Socket SP5 Rack (2U) Schwarz, Silber

Marke :
ASUS

Artikel-Code:
90SF0441-M001N0

Produktname :
RS720A-E13-RS24G

ASUS RS720A-E13-RS24G. Prozessorsocket: Socket SP5, Prozessorhersteller: AMD, Prozessorfamilie: AMD EPYC. Unterstützte Arbeitsspeicher: DDR5-SDRAM, Unterstützte DIMM-Modulkapazitäten: 16GB, 32GB, 64GB, 128GB, 256GB, RAM-Speicher maximal: 3 TB. unterstützte Speicherlaufwerksgrößen: 2.5", Unterstützte Speicherlaufwerk-Schnittstellen: SATA, Serial Attached SCSI (SAS). Eingebautes Grafikkartenmodell: Aspeed AST2600, On-board Grafikadapter-Speicher: 64 MB. Gehäusetyp: Rack (2U), Produktfarbe: Schwarz, Silber, Kühlung: Aktiv



Prozessor		Erweiterungssteckplätze	
Eingebauter Prozessor *	✗	PCI-Express-Slots-Version	5.0
Prozessorsocket *	Socket SP5	Anzahl der M.2 (M)-Steckplätze	2
Prozessorhersteller	AMD	Merkmale	
Prozessorfamilie	AMD EPYC	Trusted Platform Module (TPM)	✓
Anzahl unterstützter Prozessoren *	2	Design	
Speicher		Gehäusotyp *	Rack (2U)
Zahl der DIMM Slots *	24	Produktfarbe	Schwarz, Silber
Unterstützte Arbeitsspeicher *	DDR5-SDRAM	LED-Anzeigen	✓
Unterstützte DIMM-Modulkapazitäten	16GB, 32GB, 64GB, 128GB, 256GB	Ein-/Ausschalter	✓
RAM-Speicher maximal	3 TB	Kühlung	Aktiv
Unterstützte RDIMM Taktraten	5600,6400 MHz	Anzahl Lüfter	6 Lüfter
Speichermedium		Energie	
Anzahl der unterstützten Speicherlaufwerke *	24	Stromversorgung *	3200 W
HDD Laufwerkschächte Hot-Swap *	✓	Unterstützung für redundantes Netzteil	✓
unterstützte Speicherlaufwerksgrößen	2.5"	Anzahl der unterstützten redundanten Stromversorgungen	2
Unterstützte Speicherlaufwerk-Schnittstellen	SATA, Serial Attached SCSI (SAS)	AC Eingangsfrequenz	50/60 Hz
Grafik		80 Plus Zertifizierung	80 PLUS Titanium
Eingebautes Grafikkartenmodell	Aspeed AST2600	Betriebsbedingungen	
On-board Grafikadapter-Speicher	64 MB	Betriebstemperatur	10 - 35 °C
Netzwerk		Temperaturbereich bei Lagerung	-40 - 60 °C
Ethernet/LAN	✓	Luftfeuchtigkeit bei Lagerung	20 - 90%
		Gewicht und Abmessungen	
		Breite	484,6 mm
		Tiefe	822,2 mm
		Höhe	87,3 mm

Anschlüsse und Schnittstellen		Gewicht und Abmessungen	
USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ A	4	Gewicht	17,8 kg
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1	Verpackungsdaten	
Anzahl Mini DisplayPorts	1	Paketgewicht	21,3 kg



4711387978795

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.