



Lindy 47418 Netzwerkkabel Schwarz 10 m Cat6a S/FTP (S-STP)

Marke : Lindy

Artikel-Code: 47418

Produktname : 47418

- Twisted Pair Patchkabel mit RJ45-Stecker
 - Cat. 6A, S/FTP TPE
 - Montageschutz durch Snagless-Stecker (Klinkenschutz)
 - Vergoldete Kontakte für dauerhaft zuverlässige Steckverbindungen und Signalintegrität
- 10m Cat.6A S/FTP TPE Netzwerkkabel, schwarz

Lindy 47418 Netzwerkkabel Schwarz 10 m Cat6a S/FTP (S-STP):

- PIMF-Kabel (Paare in Metall Folie), Durchmesser: 6.0mm
- Ummantelung: TPE
- 10/100/1000/10GBase-TX-Unterstützung
- Kategorie 6A, Klasse EA, 27AWG, 4 Adernpaare
- Gigabit kompatibel sowie 10GBaseT
- Stecker: RJ45 geschirmt (blau / transparent), Snagless (Klinkenschutz), goldbeschichtete Kontakte
- belegt nach Farbcode ANSI/TIA-568-C.2
- ISO/IEC 11801:2002 / EN 50173 Class EA 500Mhz
- Fluke Cannel Test ISO 11801 Class EA
- Support PoE per IEEE 802.3af, PoE+ per IEEE 802.3at
- Farbe: schwarz

Lindy 47418. Kabellänge: 10 m, Kabelstandard: Cat6a, Kabelschirmung: S/FTP (S-STP), Anschluss 1: RJ-45, Anschluss 2: RJ-45, Beschichtung Steckerkontakte: Nickel/Gold, Produktfarbe: Schwarz



Merkmale		Merkmale	
Produktfarbe *	Schwarz	Frequenz	500 MHz
Kabellänge *	10 m	Biegeradius (min.)	7,4 cm
Kabelstandard *	Cat6a	Betriebsbedingungen	
Kabelschirmung *	S/FTP (S-STP)	Betriebstemperatur	-10 - 60 °C
Anschluss 1 *	RJ-45	Temperaturbereich bei Lagerung	-20 - 75 °C
Anschluss 2 *	RJ-45	Zertifikate	
Steckverbinder 1 Geschlecht *	Stecker	Zertifizierung	RoHS, REACH, UL, California Proposition 65
Steckverbinder 2 Geschlecht *	Stecker	Gewicht und Abmessungen	
Beschichtung Steckerkontakte	Nickel/Gold	Außendurchmesser	6,2 mm
Abschirmung Steckverbinder	✓	Stecker 1 Abmessungen (BxTxH)	11,6 x 22,8 x 8,3 mm
Material der Abschirmung des Steckverbinders	Aluminium	Stecker 2 Abmessungen (BxTxH)	11,6 x 22,8 x 8,3 mm
Mantelmaterial	Thermoplastisches Elastomer (TPE)	Verpackungsdaten	
Leitermaterial	Kupfer	Verpackungsart	Polybag
Kabel-Klasse	Ea	Logistikdaten	
Verkabelungstechnologie	10/100/1000Base-T(X)	Warentarifnummer (HS)	84733080
Netzstandard	IEEE 802.1af, IEEE 802.3af		
AWG Kabelgröße	27		



4002888474184

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.