



FSP Nano 800 Unterbrechungsfreie Stromversorgung (USV) Standby (Offline) 0,8 kVA 480 W 2 AC-Ausgänge

Marke : FSP

Artikel-Code: PPF4800305

Produktname : Nano 800

800 VA / 480W, 2 - 6 ms, 180 - 270 V, 50 / 60 Hz, 3.1 kg

FSP Nano 800 Unterbrechungsfreie Stromversorgung (USV) Standby (Offline) 0,8 kVA 480 W 2 AC-Ausgänge:

Der Nano USV liefert umfassenden Schutz in komprimierter und effizienter Form.

Der Nano USV ist kompakter und bietet wesentlich umfassenderen Schutz vor Stromausfall oder Stromspitzen.

Mit Nano kann die Stromversorgung zuverlässig fortgesetzt werden, ein sicheres Herunterfahren Ihres Pc während eines Stromausfalls ist somit ermöglicht.

Die integrierte Microprozessor Steuerung garantiert hohe Zuverlässigkeit.

- Compact size with stand and mounting flexibility
- Excellent microprocessor control guarantees high reliability
- Auto restart while AC is recovering
- Simulated sine wave
- Cold start function
- Full protection: discharge, overcharge, short circuit and thermal protection



Merkmale		Akku/Batterie	
USV-Topologie *	Standby (Offline)	Akku-/Batteriespannung	12 V
Ausgangskapazität *	0,8 kVA	Anzahl unterstützter Akkus/Batterien	1
Ausgangsleistung *	480 W	Typische Backup-Zeit bei voller Belastung	15 min
Wellenform *	Sine	Akkuladezeit	8 h
Eingangs-Betriebsspannung (min) *	180 V	Design	
Eingangs-Betriebsspannung (max) *	270 V	Formfaktor *	Kompakt
Eingangsfrequenz *	50/60 Hz	Produktfarbe *	Schwarz
Ausgangs-Betriebsspannung (min)	220 V	LED-Anzeigen	✓
Ausgangs-Betriebsspannung (max)	220 V	Gewicht und Abmessungen	
Output Frequenz	50/60 Hz	Breite	82,5 mm
Reaktionszeit	6 ms	Tiefe	228 mm
Energieschutzeigenschaften	Überlast, Tiefentladeabschaltung, Überlastschutz	Höhe	207 mm
Akustische Signale	✓	Gewicht	3,1 kg
Auto-Neustart	✓	Verpackungsdaten	
Anschlüsse und Schnittstellen		Verpackungsbreite	288 mm
AC-Steckertypen	Typ F	Verpackungstiefe	120 mm
Anzahl der AC-Ausgänge	2 AC-Ausgänge	Verpackungshöhe	280 mm
Anzahl der Typ-F Ausgänge	2	Logistikdaten	
Akku/Batterie		Warentarifnummer (HS)	85078000
Batteriekapazität	9 Ah	Sonstige Funktionen	
		Akku-/Batterietyp	9 AH
		Nominale Ausgang Spannung	220 V



4711140484785

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 29-OCT-2026. Prints or copies of Information are only valid on the printed Publication date