Canon i-SENSYS LBP6030B 2400 x 600 DPI A4



Marke : Canon **Produktfamilie:** i-SENSYS **Artikel-Code:** 8468B006

Produktname : LBP6030B



18 ppm, 600 x 600 dpi, 5000 ppm, 32 MB, USB 2.0, 49.2 dB
Canon i-SENSYS LBP6030B. Drucktechnologie: Laser. Zahl der Druckpatronen: 1, Maximale monatliche Auslastung: 5000 Seiten pro Monat. Maximale Auflösung: 2400 x 600 DPI. Maximale Papiergröße der ISO A-Serie: A4. Druckgeschwindigkeit (Schwarz, normale Qualität, A4/US Letter): 18 Seiten pro Minute. Produktfarbe: Schwarz

Drucken	
Farbe *	✕
Drucktechnologie *	Laser
Doppelseitiger Druck *	✕
Maximale Auflösung *	2400 x 600 DPI
Druckgeschwindigkeit (Schwarz, normale Qualität, A4/US Letter) *	18 Seiten pro Minute
Aufwärmzeit	10 s
Aufwärmzeit (aus dem Ruhezustand)	1 s
Druck der ersten Seite (Schwarz, normal)	7,8 s
Druckränder	5 mm

Merkmale	
Maximale monatliche Auslastung *	5000 Seiten pro Monat
Druckfarben *	Schwarz
Zahl der Druckpatronen *	1
Seitenbeschreibungssprachen *	UFRII-LT

Ein- und Ausgangskapazität	
Gesamtzahl der Papierzuführungen *	1
Gesamte Papierkapazität *	150 Blätter
Gesamte Ausgabekapazität *	100 Blätter
Art der Papierzuführung	Papierfach

Papierhandhabung	
Maximale Papiergröße der ISO A-Serie *	A4
Maximale Druckgröße	216 x 356 mm
Medientypen für das Papierfach *	Briefumschläge, Etiketten, Normales Papier, Dickes Papier, Transparenzen
ISO-A-Formate (A0...A9) *	A4, A5
ISO-B-Formate	B5
ISO C-Seriengrößen (C0...C9)	C5
Nicht-ISO Druckmedienformate	16K, Vorstand, Brief
Umschlaggrößen	10, C5, DL, Monarch
Benutzerdefinierte Medienbreite	76,2 - 216 mm
Benutzerdefinierte Medienlänge	188 - 356 mm
Mediengewichte für das Papierfach	60 - 163 g/m²

Netzwerk	
WLAN *	✕
Ethernet/LAN *	✕
Bluetooth	✕

Leistungen	
Speicherkapazität *	32 MB
Eingebauter Prozessor	✕
Schalldruckpegel (Druck)	49,2 dB
Schalldruckpegel (leiser Modus)	6,34 dB

Design	
Marktpositionierung *	Zuhause & Büro
Produktfarbe *	Schwarz
Eingebautes Display *	✕

Energie	
Durchschnittlicher Stromverbrauch beim Drucken *	330 W
Stromverbrauch (max.)	870 W
Stromverbrauch (Standby)	1,8 W
Stromverbrauch (PowerSave)	0,8 W
Energy Star Typischer Stromverbrauch (TEC)	0,47 kWh/Woche
AC Eingangsspannung	220 - 240 V
AC Eingangsfrequenz	50 - 60 Hz

Anschlüsse und Schnittstellen	
Standard-Schnittstellen	USB 2.0
USB Anschluss *	✔
Anzahl USB 2.0 Anschlüsse	1

Systemanforderung	
Unterstützt Windows-Betriebssysteme	Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Unterstützt Mac-Betriebssysteme	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Unterstützte Linux-Betriebssysteme	✔
Unterstützte Server-Betriebssysteme	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2 x64, Windows Server 2008 x64, Windows Server 2012, Windows Server 2012 R2, Windows Server 2012 R2 x64, Windows Server 2012 x64

Betriebsbedingungen	
Betriebstemperatur	10 - 30 °C
Relative Luftfeuchtigkeit in Betrieb	20 - 80%

Nachhaltigkeit	
Nachhaltigkeitszertifikate	ENERGY STAR

Gewicht und Abmessungen	
Breite	364 mm
Tiefe	249 mm
Höhe	199 mm
Gewicht	5 kg

Logistikdaten	
Warentarifnummer (HS)	84433210

Sonstige Funktionen	
Power-LED	✔

4960999996615

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-SEP-2026. Prints or copies of Information are only valid on the printed Publication date