



LevelOne IEC-4001 Netzwerk Medienkonverter 100 Mbit/s Multi-Modus Schwarz

Marke : LevelOne

Artikel-Code: IEC-4001

Produktname : IEC-4001



LevelOne IEC-4001. Maximale Datenübertragungsrate: 100 Mbit/s, Converter Eingangsschnittstelle: 10Base-T, 100Base-TX, Converter output Oberfläche: 100Base-FX. Maximal mögliche Übertragungsstrecke: 2000 m, Kabel mode struktur: Multi-Modus. LED-Anzeigen: Aktivität, Leistung, Status, Produktfarbe: Schwarz, Gehäusematerial: Aluminium. Optischer Kabelverbinder: SC, Übertragungstechnik: Kabelgebunden. Eingangsspannung: 12 - 60 V, Stromverbrauch (Standardbetrieb): 1,44 W



Netzwerk		Energie	
Maximale Datenübertragungsrate *	100 Mbit/s	Stromverbrauch (Standardbetrieb)	1,44 W
Converter Eingangsschnittstelle	10Base-T, 100Base-TX	Gewicht und Abmessungen	
Converter output Oberfläche	100Base-FX	Breite	59 mm
Netzstandard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Tiefe	49 mm
Ethernet Schnittstellen Typ	Schnelles Ethernet	Höhe	36 mm
Ethernet LAN Datentransferraten	10,100 Mbit/s	Gewicht	90 g
Auto MDI/MDI-X	✓	Betriebsbedingungen	
Auto-Negotiation-Funktion	✓	Betriebstemperatur	-40 - 75 °C
Store-and-Forward	✓	Temperaturbereich bei Lagerung	-40 - 75 °C
Duplex-System	Voll, Halb	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Leistungen		Lieferumfang	
Maximal mögliche Übertragungsstrecke *	2000 m	Schnellinstallationsanleitung	✓
Kabel mode struktur	Multi-Modus	Verpackungsdaten	
Merkmale		Verpackungsbreite	160 mm
Eingebaut *	✗	Verpackungstiefe	105 mm
LED-Anzeigen	Aktivität, Leistung, Status	Verpackungshöhe	65 mm
Produktfarbe	Schwarz	Paketgewicht	260 g
Gehäusematerial	Aluminium	Verpackungsart	Box
Anschlüsse und Schnittstellen		Zertifikate	
Übertragungstechnik	Kabelgebunden	Zertifizierung	FCC Part 15 Subpart B Class A CE
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1		EN 55022 Class A FCC Part 15 Subpart B Class A, CE EN 55022 Class A EN61000-4-2 (ESD) Level 3
Anzahl Faseranschlüsse	1		EN61000-4-3 (RS) Level 2
Optischer Kabelverbinder *	SC		EN61000-4-4 (EFT) Level 2
			EN61000-4-5 (Surge) Level 2
Energie			EN61000-4-6 (CS) Level 2 EN 61000-4-8 (PFMF) Level 1 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6
Eingangsspannung	12 - 60 V	Logistikdaten	
		Ursprungsland	Taiwan
		Warentarifnummer (HS)	85176990



4015867188149

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.