



TP-Link Archer TX55E WLAN / Bluetooth 2402 Mbit/s

Marke : TP-Link

Produktfamilie: Archer

Artikel-Code: ARCHER TX55E

Produktname : Archer TX55E

TP-Link Archer TX55E. Übertragungstechnik: Kabellos, Hostschnittstelle: PCI Express, Schnittstelle: WLAN / Bluetooth. Maximale Datenübertragungsrate: 2402 Mbit/s, Top WLAN-Standard: Wi-Fi 6 (802.11ax), WLAN-Band: Dual-Band (2,4 GHz/5 GHz). Produktfarbe: Schwarz



Anschlüsse und Schnittstellen		Systemanforderung	
Übertragungstechnik *	Kabellos	Unterstützt Windows-Betriebssysteme	Windows 10 Education x64, Windows 10 Enterprise x64, Windows 10 Home x64, Windows 10 Pro x64, Windows 10 x64
Hostschnittstelle *	PCI Express		
Schnittstelle *	WLAN / Bluetooth		
USB-Version	2.0		
Netzwerk		Betriebsbedingungen	
Maximale Datenübertragungsrate *	2402 Mbit/s	Betriebstemperatur	0 - 40 °C
Netzstandard *	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11g, IEEE 802.11n	Temperaturbereich bei Lagerung	-40 - 70 °C
		Relative Luftfeuchtigkeit in Betrieb	10 - 90%
		Luftfeuchtigkeit bei Lagerung	5 - 90%
		Nachhaltigkeit	
WLAN	✓	Nachhaltigkeitskonformität	✓
WLAN-Band	Dual-Band (2,4 GHz/5 GHz)	Gewicht und Abmessungen	
Frequenzbereich	2,4 - 5 GHz	Breite	120 mm
Top WLAN-Standard	Wi-Fi 6 (802.11ax)	Tiefe	78,5 mm
WLAN-Standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Höhe	21 mm
		Verpackungsdaten	
Datenübertragungsgeschwindigkeit WLAN	11,54,300,574,1733,2402 Mbit/s	Verpackungsbreite	201,5 mm
Modulation	16-QAM, 64-QAM, 256-QAM, 1024-QAM, CCK, DQPSK, OFDM	Verpackungstiefe	152,5 mm
		Verpackungshöhe	41,5 mm
Unterstützte Sicherheitsalgorithmen	64-bit WEP, 128-bit WEP, 802.1x RADIUS, WPA, WPA-PSK, WPA2, WPA2-PSK, WPA3	Paketgewicht	230 g
		Lieferumfang	
Bluetooth	✓	Montageblöcke enthalten	✓
Bluetooth-Version	5.2	Ressourcen-CD	✓
Design		Bluetooth-Header-Kabel	✓
Produktfarbe	Schwarz	Schnellinstallationsanleitung	✓
Eingebaut *	✗	Technische Details	
Antenne	✓	Konformitätsbescheinigungen	CE, Eidgenössische Kommunikationskommission (FCC), RoHS
Antennen-Design	Extern		
Sendeleistung (CE)	23 dbm		
Sendeleistung (FCC)	27 dbm		
Betriebsmodi	Infrastrukturmodus		



4897098687390



0840030707391



840030707391



4897098687253

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.