



D-Link DGS-1210-28 Managed L2/L2+ 1U Schwarz

Marke : D-Link

Artikel-Code: DGS-1210-28/E

Produktname : DGS-1210-28



24x 10/100/1000BASE-T RJ-45, 4x 100/1000 Mbps combo, 56 Gbps, 41.7 Mpps, 8K MAC, 440 x 140 x 44 mm

D-Link DGS-1210-28. Switch-Typ: Managed, Switch-Ebene: L2/L2+. Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24. Vollduplex. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 56 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Rack-Einbau, Formfaktor: 1U

| Management-Funktionen                              |                                                    | Energie                              |                                                               |
|----------------------------------------------------|----------------------------------------------------|--------------------------------------|---------------------------------------------------------------|
| Switch-Typ *                                       | Managed                                            | Stromverbrauch (Standardbetrieb)     | 16,81 W                                                       |
| Switch-Ebene                                       | L2/L2+                                             | Betriebsbedingungen                  |                                                               |
| Anschlüsse und Schnittstellen                      |                                                    | Betriebstemperatur                   | -5 - 50 °C                                                    |
| Anzahl der basisschaltenden RJ-45 Ethernet Ports * | 24                                                 | Temperaturbereich bei Lagerung       | -20 - 70 °C                                                   |
| Netzwerk                                           |                                                    | Relative Luftfeuchtigkeit in Betrieb | 0 - 95%                                                       |
| Netzstandard *                                     | IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x | Gewicht und Abmessungen              |                                                               |
| Vollduplex                                         | ✓                                                  | Breite                               | 440 mm                                                        |
| Datenübertragung                                   |                                                    | Tiefe                                | 210 mm                                                        |
| Routing-/Switching-Kapazität *                     | 56 Gbit/s                                          | Höhe                                 | 44 mm                                                         |
| MAC-Adressentabelle *                              | 16000 Eintragungen                                 | Gewicht                              | 2,9 kg                                                        |
| Design                                             |                                                    | Verpackungsdaten                     |                                                               |
| Rack-Einbau *                                      | ✓                                                  | Verpackungsbreite                    | 249 mm                                                        |
| Formfaktor                                         | 1U                                                 | Verpackungstiefe                     | 493 mm                                                        |
| Produktfarbe                                       | Schwarz                                            | Verpackungshöhe                      | 72 mm                                                         |
| LED-Anzeigen                                       | ✓                                                  | Paketgewicht                         | 3,24 kg                                                       |
| Leistungen                                         |                                                    | Zertifikate                          |                                                               |
| Mittlere Betriebsdauer zwischen Ausfällen (MTBF)   | 236739 h                                           | Zertifizierung                       | FCC Class A, CE Class A, ICES-003, VCCI Class A, C-Tick, BSMI |
| Energie                                            |                                                    |                                      |                                                               |
| AC Eingangsspannung                                | 100 - 240 V                                        |                                      |                                                               |



0790069467769



790069467769



5704174940388

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.