

## CyberPower MBP20HVIEC6A Maintenance Bypass PDU Rack 1U, Eingang 16A- (1) IEC C19 + (2) IEC C20, Ausgang 16A- (6) IEC C13 + (1) IEC C19 für OL + OLSA Rackmount

**Marke :** CyberPower

**Artikel-Code:** MBP20HVIEC6A

**Produktname :** MBP20HVIEC6A Maintenance Bypass PDU  
Rack 1U, Eingang 16A- (1) IEC C19 + (2) IEC C20, Ausgang  
16A- (6) IEC C13 + (1) IEC C19 für OL + OLSA Rackmount

MBP20HVIEC6A Maintenance Bypass PDU Rack 1U, Eingang 16A- (1) IEC C19 + (2) IEC C20, Ausgang  
16A- (6) IEC C13 + (1) IEC C19 für OL + OLSA Rackmount

CyberPower MBP20HVIEC6A Maintenance Bypass PDU Rack 1U, Eingang 16A- (1) IEC C19 + (2) IEC C20,  
Ausgang 16A- (6) IEC C13 + (1) IEC C19 für OL + OLSA Rackmount:

CyberPower MBP20HVIEC6A ist für den Anschluß an eine USV zu Wartungszwecken an dieser konzipiert  
und wechselt bei Umschaltung die Stromversorgung der Endgeräte von der USV zur Stromversorgung  
aus der Netzversorgung. Der MBP beinhaltet eine PDU mit mehreren Ausgangssteckdosen für den  
Anschluß mehrerer Geräte. Der MBP ist in verschiedenen Versionen für flexiblen Stand- oder Rackeinbau  
erhältlich.



| Merkmale                    |                                                                                                                                                                                                  | Betriebsbedingungen                  |             |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|-------------|
| Produkttyp *                | Überbrückungsschalter                                                                                                                                                                            | Temperaturbereich bei Lagerung       | -15 - 45 °C |
| Befestigungstyp             | Rack-montierbar                                                                                                                                                                                  | Relative Luftfeuchtigkeit in Betrieb | 0 - 90%     |
| Produktfarbe                | Schwarz                                                                                                                                                                                          | Luftfeuchtigkeit bei Lagerung        | 0 - 95%     |
| LED-Anzeigen                | Status                                                                                                                                                                                           | Höhe bei Betrieb                     | 0 - 3000 m  |
| Gehäusematerial             | Metall                                                                                                                                                                                           | Höhe bei Lagerung                    | 0 - 15000 m |
| Rack-Kapazität              | 1U                                                                                                                                                                                               | Gewicht und Abmessungen              |             |
| Kompatibilität              | OL1000ERTXL2U, OL1500ERTXL2U, OL2000ERTXL2U, OL3000ERTXL2U, OLS1000ERT2U, OLS1500ERT2U, OLS2000ERT2U, OLS3000ERT2U, OLS6000ERTXL3U, OLS10000ERTXL3U, OLS1000ERT2UA, OLS2000ERT2UA, OLS3000ERT2Ua | Breite                               | 433 mm      |
|                             |                                                                                                                                                                                                  | Tiefe                                | 76 mm       |
|                             |                                                                                                                                                                                                  | Höhe                                 | 51 mm       |
|                             |                                                                                                                                                                                                  | Gewicht                              | 1,3 kg      |
|                             |                                                                                                                                                                                                  | Verpackungsdaten                     |             |
| <b>Energie</b>              |                                                                                                                                                                                                  | Verpackungsbreite                    | 245 mm      |
|                             |                                                                                                                                                                                                  | Verpackungstiefe                     | 500 mm      |
|                             |                                                                                                                                                                                                  | Verpackungshöhe                      | 66 mm       |
|                             |                                                                                                                                                                                                  | Paketgewicht                         | 3,5 kg      |
| <b>Nachhaltigkeit</b>       |                                                                                                                                                                                                  | Logistikdaten                        |             |
|                             |                                                                                                                                                                                                  | Garantiezeit                         | 2 Jahr(e)   |
| Nachhaltigkeitskonformität  |                                                                                                                                                                                                  | ✓                                    |             |
| Zertifikate                 |                                                                                                                                                                                                  |                                      |             |
| Konformitätsbescheinigungen | CE, RoHS                                                                                                                                                                                         |                                      |             |
| Betriebsbedingungen         |                                                                                                                                                                                                  |                                      |             |
| Betriebstemperatur          | 0 - 40 °C                                                                                                                                                                                        |                                      |             |



4711027799858

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.