



Lindy 47421 Netzwerkkabel Schwarz 30 m Cat6a S/FTP (S-STP)

Marke : Lindy

Artikel-Code: 47421

Produktname : 47421

- Twisted Pair Patchkabel mit RJ45-Stecker
 - Cat.6A, S/FTP TPE
 - Montageschutz durch Snagless-Stecker (Klinkenschutz)
 - Vergoldete Kontakte für dauerhaft zuverlässige Steckverbindungen und Signalintegrität
- 30m Cat.6A S/FTP TPE Netzwerkkabel, schwarz

Lindy 47421 Netzwerkkabel Schwarz 30 m Cat6a S/FTP (S-STP):

Assembled Cat.6A S / FTP TPE patch cable

- PIMF cable (pairs in metal foil), diameter: 6.0mm
- Sheath: TPE
- 10/100/1000 / 10GBase-TX support
- Category 6A, class EA, 27AWG, 4 wire pairs
- Gigabit compatible as well as 10GBaseT
- Connector: RJ45 shielded (blue / transparent), Snagless (latch protection), gold-plated contacts
- Occupied by color code ANSI / TIA-568-C.2
- ISO / IEC 11801: 2002 / EN 50173 Class EA 500Mhz
- Fluke Cannel Test ISO 11801 Class EA
- Support PoE per IEEE 802.3af, PoE + per IEEE 802.3at
- Color: Black

Lindy 47421. Kabellänge: 30 m, Kabelstandard: Cat6a, Kabelschirmung: S/FTP (S-STP), Anschluss 1: RJ-45, Anschluss 2: RJ-45, Beschichtung Steckerkontakte: Nickel/Gold, Produktfarbe: Schwarz



Merkmale		Merkmale	
Produktfarbe *	Schwarz	Biegeradius (min.)	7,4 cm
Kabellänge *	30 m	Betriebsbedingungen	
Kabelstandard *	Cat6a	Betriebstemperatur	-10 - 60 °C
Kabelschirmung *	S/FTP (S-STP)	Temperaturbereich bei Lagerung	-20 - 75 °C
Anschluss 1 *	RJ-45	Zertifikate	
Anschluss 2 *	RJ-45	Zertifizierung	RoHS, REACH, UL, California Proposition 65
Steckverbinder 1 Geschlecht *	Stecker	Gewicht und Abmessungen	
Steckverbinder 2 Geschlecht *	Stecker	Außendurchmesser	6,2 mm
Beschichtung Steckerkontakte	Nickel/Gold	Stecker 1 Abmessungen (BxTxH)	11,6 x 22,8 x 8,3 mm
Abschirmung Steckverbinder	✓	Stecker 2 Abmessungen (BxTxH)	11,6 x 22,8 x 8,3 mm
Material der Abschirmung des Steckverbinders	Aluminium	Verpackungsdaten	
Mantelmaterial	Thermoplastisches Elastomer (TPE)	Verpackungsart	Polybag
Leitermaterial	Kupfer	Sonstige Funktionen	
Kabel-Klasse	Ea	Kabeldurchmesser	6 mm
Verkabelungstechnologie	10/100/1000Base-T(X)	Logistikdaten	
Netzstandard	IEEE 802.3af, IEEE 802.3at	Warentarifnummer (HS)	84733080
AWG Kabelgröße	27		
Frequenz	500 MHz		



4002888474214

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.