



TP-Link EAP650-DESKTOP(EU) WLAN Access Point 2976 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Artikel-Code: EAP650-DESKTOP(EU)

Produktname : EAP650-DESKTOP(EU)

TP-Link EAP650-DESKTOP(EU). 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 2976 Mbit/s.
Unterstützte Sicherheitsalgorithmen: 802.1x RADIUS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise,
WPA-Personal, WPA2-Enterprise,.... Ethernet LAN Datentransferraten: 1000 Mbit/s. Power over Ethernet
(PoE). Produktfarbe: Weiß. Stromverbrauch (max.): 17,3 W



Merkmale		Anschlüsse und Schnittstellen	
2,4 GHz *	✓	Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	4
5 GHz *	✓	Energie	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximale Datenübertragungsrate *	2976 Mbit/s	DC Spannungsrage	12 V
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s	Eingangsstrom	1.5 A
Maximale Datenübertragungsrate (5 GHz)	2402 Mbit/s	Stromverbrauch (max.)	17,3 W
Ethernet LAN Datentransferraten	1000 Mbit/s	Design	
Netzstandard	IEEE 802.3af, IEEE 802.3bt	Platzierung *	Tisch
Kanalabstand	160 MHz	Produktfarbe *	Weiß
MIMO	✓	Reset-Knopf	✓
MIMO-Typ	Multi User MIMO	LED-Anzeigen	✓
VLAN-Unterstützung	✓	Antenne	
Ratenbeschränkung	✓	Antennentyp *	Intern
Lastausgleich	✓	Antenne Zunahmehniveau (max)	4,7 dBi
Bandsteuerung	✓	Leistungen	
Airtime Fairness (ATF)	✓	Kompatible Betriebssysteme	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Quality of Service (QoS) Support	✓	Zertifikate	
BeamForming	✓	Zertifizierung	CE, FCC, RoHS, IC
Sendeleistung (CE)	20 - 29 dbm	Gewicht und Abmessungen	
Sendeleistung (FCC)	26 - 27 dbm	Breite	140 mm
Sicherheit		Tiefe	33 mm
Unterstützte Sicherheitsalgorithmen *	802.1x RADIUS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal	Höhe	175 mm
		Gewicht	452 g

Sicherheit		Lieferumfang	
Funktionen Service Set Identifier (SSID)	Multiple SSIDs	Menge pro Packung	1 Stück(e)
Anzahl der SSID-Unterstützung	16	Sonstige Funktionen	
Zugriffskontrollliste	✓	Drahtloser Standard	IEEE 802.11 a/b/g/n/ac/ax
Management-Funktionen		Betriebsbedingungen	
Web-basiertes Management	✓	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Syslog	✓	Betriebstemperatur	0 - 40 °C
Management-Plattform	Omada	Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.