



TP-Link TL-SG1016(UN) Netzwerk-Switch Unmanaged Gigabit Ethernet (10/100/1000) 1U Schwarz

Marke : TP-Link

Artikel-Code: TL-SG1016(UN)

Produktname : TL-SG1016(UN)

TP-Link TL-SG1016(UN). Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 16. Vollduplex. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 32 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Rack-Einbau, Formfaktor: 1U



Management-Funktionen		Sicherheit		
Switch-Typ *	Unmanaged	Unterstützte Sicherheitsalgorithmen	802.1x RADIUS	
Quality of Service (QoS) Support	✓	Passwortschutz	✓	
Anschlüsse und Schnittstellen		Design		
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	16	Rack-Einbau *	✓	
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Formfaktor	1U	
Netzwerk		Produktfarbe	Schwarz	
		LED-Anzeigen	Aktivität, Link, Leistung	
	Leistungen			
	Netzstandard *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Ventilatorlos	✓
	Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Energie	
unterstützte Kabeltypen	Cat3, Cat4, Cat5, Cat5e	AC Eingangsspannung	100 - 240 V	
Port-Spiegelung	✓	Stromverbrauch (Standardbetrieb)	9,26 W	
Vollduplex	✓	Stromverbrauch (max.)	10,44 W	
IP-Routing	✓	Power over Ethernet (PoE)		
Richtlinienbasiertes Routing	✓	Power over Ethernet (PoE) *	✗	
Unterstützung Datenflusssteuerung	✓	Betriebsbedingungen		
Auto MDI/MDI-X	✓	Betriebstemperatur	0 - 40 °C	
Head-of-Line (HOL)-Blocking	✓	Temperaturbereich bei Lagerung	-40 - 70 °C	
Ethernet LAN Datentransferraten	10,100,480,800,1000 Mbit/s	Relative Luftfeuchtigkeit in Betrieb	10 - 90%	
Auto-Negotiation-Funktion	✓	Luftfeuchtigkeit bei Lagerung	5 - 90%	
VLAN-Unterstützung	✓	Wärmeableitung	35,6 BTU/h	
Datenübertragung		Gewicht und Abmessungen		
Routing-/Switching-Kapazität *	32 Gbit/s	Breite	440 mm	
Transferrate	23,8 Mpps	Tiefe	180 mm	
MAC-Adressentabelle *	8000 Eintragungen	Höhe	44 mm	
Store-and-Forward	✓	Lieferumfang		
Jumbo Frames Unterstützung	✓	Mitgelieferte Kabel	AC	
Jumbo-Frames	10000	Rackmontageset	✓	

Sicherheit		Zertifikate	
DHCP-Funktionen	DHCP client, DHCP server, DHCP snooping	Zertifizierung	FCC, CE, RoHS
Zugriffskontrollliste	✓	Logistikdaten	
IGMP-Snooping	✓	Warentarifnummer (HS)	85176990

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.