



# Lindy 47341 Netzwerkkabel Grau 0,3 m Cat6 S/FTP (S-STP)

Marke : Lindy

Artikel-Code: 47341

Produktname : 47341


- Twisted Pair Patchkabel mit RJ45-Stecker
  - Cat.6, S/FTP
  - Montageschutz durch Snagless-Stecker (Klinkenschutz)
  - Vergoldete Kontakte für dauerhaft zuverlässige Steckverbindungen und Signalintegrität
- 0.5m Cat.6 S/FTP Netzwerkkabel, grau

Lindy 47341 Netzwerkkabel Grau 0,3 m Cat6 S/FTP (S-STP):

### Konfektioniertes S/FTP Patchkabel

- PIMF-Kabel (Paare in Metall Folie)
- 10/100/1000Base-TX-Unterstützung
- Kategorie 6, 28 AWG, 4 Adernpaare
- Gigabit kompatibel
- Stecker: RJ45 geschirmt, Snagless (Klinkenschutz), goldbeschichtete Kontakte
- belegt nach Farbcode ANSI/TIA-568-C.2
- Farbe: grau

Lindy 47341. Kabellänge: 0,3 m, Kabelstandard: Cat6, Kabelschirmung: S/FTP (S-STP), Anschluss 1: RJ-45, Anschluss 2: RJ-45, Beschichtung Steckerkontakte: Nickel/Gold, Produktfarbe: Grau



| Merkmale                                     |                        | Merkmale                       |                                            |
|----------------------------------------------|------------------------|--------------------------------|--------------------------------------------|
| Produktfarbe *                               | Grau                   | Biegeradius (min.)             | 7,4 cm                                     |
| Kabellänge *                                 | 0,3 m                  | Betriebsbedingungen            |                                            |
| Kabelstandard *                              | Cat6                   | Betriebstemperatur             | -10 - 60 °C                                |
| Kabelschirmung *                             | S/FTP (S-STP)          | Temperaturbereich bei Lagerung | -20 - 75 °C                                |
| Anschluss 1 *                                | RJ-45                  | Zertifikate                    |                                            |
| Anschluss 2 *                                | RJ-45                  | Zertifizierung                 | RoHS, REACH, UL, California Proposition 65 |
| Steckverbinder 1 Geschlecht *                | Stecker                | Gewicht und Abmessungen        |                                            |
| Steckverbinder 2 Geschlecht *                | Stecker                | Außendurchmesser               | 6,2 mm                                     |
| Beschichtung Steckerkontakte                 | Nickel/Gold            | Stecker 1 Abmessungen (BxTxH)  | 22,8 x 11,6 x 8,3 mm                       |
| Abschirmung Steckverbinder                   | ✓                      | Stecker 2 Abmessungen (BxTxH)  | 22,8 x 11,6 x 8,3 mm                       |
| Material der Abschirmung des Steckverbinders | Aluminium              | Verpackungsdaten               |                                            |
| Mantelmaterial                               | Polyvinylchlorid (PVC) | Verpackungsart                 | Polybag                                    |
| Leitermaterial                               | Kupfer                 | Logistikdaten                  |                                            |
| Verkabelungstechnologie                      | 10/100/1000Base-T(X)   | Warentarifnummer (HS)          | 84733080                                   |
| AWG Kabelgröße                               | 28                     |                                |                                            |
| Frequenz                                     | 250 MHz                |                                |                                            |



4002888473415

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.