



## TP-Link RE450 Netzwerk-Repeater Weiß 10, 100, 1000 Mbit/s

**Marke :** TP-Link

**Artikel-Code:** RE450 V2

**Produktname :** RE450

IEEE802.11ac/n/g/b, Ethernet, 2,4 - 5 GHz

TP-Link RE450. Typ: Netzwerk-Repeater, Datenübertragungsrate: 1300 Mbit/s, Ethernet LAN

Datentransferraten: 10,100,1000 Mbit/s. Antennentyp: Extern. Verkabelungstechnologie:

10/100/1000Base-T(X), Netzstandard: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, WLAN-Standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac).

Produktfarbe: Weiß, Zertifizierung: CE, FCC. AC Eingangsspannung: 100 - 240 V, AC Eingangsfrequenz: 50 - 60 Hz, Stromverbrauch (max.): 9 W



| Leistungen                          |                                                                                                   | Design                               |             |
|-------------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------|-------------|
| Typ *                               | Netzwerk-Repeater                                                                                 | Ein-/Ausschalter                     | ✓           |
| Datenübertragungsrate               | 1300 Mbit/s                                                                                       | Reset-Knopf                          | ✓           |
| Ethernet LAN Datentransferraten     | 10,100,1000 Mbit/s                                                                                | Zertifizierung                       | CE, FCC     |
| Unterstützt Windows-Betriebssysteme | Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows XP | Energie                              |             |
| Mac-Kompatibilität                  | ✓                                                                                                 | AC Eingangsspannung                  | 100 - 240 V |
| Unterstützt Mac-Betriebssysteme     | ✓                                                                                                 | AC Eingangsfrequenz                  | 50 - 60 Hz  |
| Unterstützte Linux-Betriebssysteme  | ✓                                                                                                 | Stromverbrauch (max.)                | 9 W         |
| Antenne                             |                                                                                                   | Betriebsbedingungen                  |             |
| Anzahl der Antennen                 | 3                                                                                                 | Betriebstemperatur                   | 0 - 40 °C   |
| Antennentyp                         | Extern                                                                                            | Temperaturbereich bei Lagerung       | -40 - 70 °C |
| Netzwerk                            |                                                                                                   | Relative Luftfeuchtigkeit in Betrieb | 10 - 90%    |
| Verkabelungstechnologie             | 10/100/1000Base-T(X)                                                                              | Luftfeuchtigkeit bei Lagerung        | 5 - 90%     |
| Netzstandard                        | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n                             | Gewicht und Abmessungen              |             |
| WLAN                                | ✓                                                                                                 | Breite                               | 163 mm      |
| WLAN-Standards                      | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)                                  | Tiefe                                | 76,4 mm     |
| Wi-Fi Datenrate (max)               | 1300 Mbit/s                                                                                       | Höhe                                 | 66,5 mm     |
| WLAN-Band                           | Dual-Band (2,4 GHz/5 GHz)                                                                         | Gewicht                              | 230 g       |
|                                     |                                                                                                   | Lieferumfang                         |             |
|                                     |                                                                                                   | Mitgelieferte Kabel                  | LAN (RJ-45) |
|                                     |                                                                                                   | Schnellstartübersicht                | ✓           |

| Netzwerk                               |                                            | Verpackungsdaten            |        |
|----------------------------------------|--------------------------------------------|-----------------------------|--------|
| Unterstützte Sicherheitsalgorithmen    | 128-bit WEP, 64-bit WEP, WPA-PSK, WPA2-PSK | Verpackungsbreite           | 202 mm |
| Anschlüsse und Schnittstellen          |                                            | Verpackungstiefe            | 125 mm |
|                                        |                                            | Verpackungshöhe             | 86 mm  |
|                                        |                                            | Paketgewicht                | 350 g  |
| Anzahl Ethernet-LAN-Anschlüsse (RJ-45) | 1                                          | Zertifikate                 |        |
| Design                                 |                                            | Konformitätsbescheinigungen | RoHS   |
| Produktfarbe *                         | Weiß                                       |                             |        |
| LED-Anzeigen                           | ✓                                          |                             |        |



6935364092382



0845973092405



845973092405



6935364095994

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.