

ZYXEL

Zyxel GS-1900-24 v2 Managed L2 Gigabit Ethernet (10/100/1000) 1U Schwarz

Marke : Zyxel

Artikel-Code: GS1900-24-EU0102F

Produktname : GS-1900-24 v2

Zyxel GS-1900-24 v2. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24. Vollduplex. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 52 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE.... Netzstecker: AC-Eingangsbuchse. Rack-Einbau, Formfaktor: 1U



Management-Funktionen		Design	
Switch-Typ *	Managed	Rack-Einbau *	✓
Switch-Ebene	L2	Stapelbar *	✓
Quality of Service (QoS) Support	✓	Formfaktor	1U
Web-basiertes Management	✓	Produktfarbe	Schwarz
Systemereignisprotokoll	✓	Reset-Knopf	✓
MIB Unterstützung	RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215, RFC 1493	LED-Anzeigen	✓
Anschlüsse und Schnittstellen		Leistungen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	432,673 h
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Energie	
Menge SFP-Modul-Steckplätze	2	Energiequelle *	AC
Netzstecker	AC-Eingangsbuchse	Netzteil enthalten *	✓
Netzwerk		AC Eingangsspannung	100 - 240 V
Netzstandard *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	AC Eingangsfrequenz	50 - 60 Hz
		Stromverbrauch (max.)	16 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✗
		Betriebsbedingungen	
10G-Unterstützung *	✗	Betriebstemperatur	0 - 50 °C
Port-Spiegelung	✓	Temperaturbereich bei Lagerung	-40 - 70 °C
Vollduplex	✓	Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Unterstützung Datenflusssteuerung	✓	Luftfeuchtigkeit bei Lagerung	10 - 95%
Link Aggregation	✓	Wärmeableitung	55 BTU/h
Spannbaum-Protokoll	✓	Gewicht und Abmessungen	
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Breite	440 mm
		Tiefe	131 mm

Netzwerk		Gewicht und Abmessungen	
Selbstlernen von MAC-Adressen unterstützt	✓	Höhe	44 mm
VLAN-Unterstützung	✓	Gewicht	2,09 kg
Virtuelle LAN-Funktionen	Tagged VLAN, VLAN Identifier (VLAN ID), Voice VLAN	Lieferumfang	
Datenübertragung		Mitgelieferte Kabel	AC
Routing-/Switching-Kapazität *	52 Gbit/s	Rackmontageset	✓
Transferrate	39 Mpps	Verpackungsdaten	
MAC-Adressentabelle *	8000 Eintragungen	Verpackungsart	Box
Store-and-Forward	✓	Verpackungsbreite	561 mm
Jumbo Frames Unterstützung	✓	Verpackungstiefe	217 mm
Jumbo-Frames	9000	Verpackungshöhe	82 mm
Datenpaket-Pufferspeicher	0,525 MB	Paketgewicht	2,85 kg
Sicherheit		Zertifikate	
DHCP-Funktionen	DHCP client	Zertifizierung	EMC ■ CE, FCC, C-Tick, Class A (GS1900-24/24EP/24HPv2/48/48HPv2) ■ CE, FCC, C-Tick, Class B (GS1900-8/8HP/10HP/16/24E) ■ BSMI CNS13438 • Safety ■ LVD EN60950-1 ■ BSMI CNS14336-1 ■ CB IEC60950-1 (GS1900-8HP/10HP/16/24E/24) • RoHS compliant
IGMP-Snooping	✓		
Unterstützte Sicherheitsalgorithmen	802.1x RADIUS		
MAC Adressen Filtern	✓		
Statische Anschlusssicherheit	✓		
SSH-/SSL-Unterstützung	✓	Logistikdaten	
Passwortschutz	✓	Warentarifnummer (HS)	85176990
Autentifizierungstyp	RADIUS, TACACS+		



4718937621231

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.