



D-Link DGS-1510-52XMP Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz



Marke : D-Link

Artikel-Code: DGS-1510-52XMP/E

Produktname : DGS-1510-52XMP

D-Link DGS-1510-52XMP. Switch-Typ: Managed, Switch-Ebene: L3. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 48. Vollduplex. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 128 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE). Rack-Einbau

Management-Funktionen		Design	
Switch-Typ *	Managed	Produktfarbe	Schwarz
Switch-Ebene	L3	Reset-Knopf	✓
Quality of Service (QoS) Support	✓	LED-Anzeigen	Aktivität, Link, PoE, Geschwindigkeit
Web-basiertes Management	✓	Anzahl Lüfter	3 Lüfter
Traffic-Klassifizierung	✓	Leistungen	
ARP-Inspektion	✓	Geräuschpegel	56,9 dB
Anschlüsse und Schnittstellen		Energie	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	48	Netzteil enthalten *	✓
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	AC Eingangsspannung	100 - 240 V
Menge Modul-Steckplätze SFP+	4	Stromverbrauch (max.)	486,9 W
Netzwerk		Power over Ethernet (PoE)	
Netzstandard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) *	✓
10G-Unterstützung *	✓	Betriebsbedingungen	
unterstützte Kabeltypen	Cat5, Cat5e	Betriebstemperatur	-5 - 50 °C
Vollduplex	✓	Temperaturbereich bei Lagerung	-20 - 70 °C
Auto MDI/MDI-X	✓	Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Datenübertragung		Luftfeuchtigkeit bei Lagerung	0 - 95%
Routing-/Switching-Kapazität *	128 Gbit/s	Wärmeableitung	138,787 BTU/h
Durchgang	95,24 Mpps	Gewicht und Abmessungen	
MAC-Adressentabelle *	16000 Eintragungen	Breite	440 mm
Anzahl IP-Schnittstellen	16	Tiefe	308 mm
Jumbo Frames Unterstützung	✓	Höhe	44 mm
Jumbo-Frames	9216	Gewicht	5,41 kg
Multicast-Funktionen		Verpackungsdaten	
Multicast Unterstützung	✓	Verpackungsbreite	475 mm
Multicast MAC-Adresstabelle	512 Eintragungen	Verpackungstiefe	520 mm
Design		Verpackungshöhe	110 mm
Rack-Einbau *	✓	Paketgewicht	7,26 kg
Stapelbar *	✓	Zertifikate	
		Zertifizierung	CE FCC C-Tick VCCI BSMI cUL CB



0790069467967



790069467967



5704174940524

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.