



LevelOne 24V DC Industrie-Netzteil, 120W, DIN-Schiene,-20 ~ +70 °C

Marke : LevelOne

Artikel-Code: POW-2442

Produktname : 24V DC Industrie-Netzteil, 120W, DIN-Schiene,-20 ~ +70 °C



- Universeller AC-Eingang im gesamten Bereich
- Kurzschluss-, Überlast- und Überspannungsschutz
- Lüfterloses Design unterstützt
- DIN-Schieneninstallation
- 100% Volllast

- Burn-in-Test mit DC OK Relaiskontakt2

24V DC Industrie-Netzteil, 120W, DIN-Schiene,-20 ~ +70 °C

LevelOne 24V DC Industrie-Netzteil, 120W, DIN-Schiene,-20 ~ +70 °C. Gesamtleistung: 120 W, AC Eingangsspannung: 90 -264 V, AC Eingangsfrequenz: 47 - 63 Hz. Mittlere Betriebsdauer zwischen Ausfällen (MTBF): 2636800 h. Produktfarbe: Blau, Silber. Sicherheit: EN 55032 (CISPR32) Class A EN 61000-3-2,-3,EACTPTC020,CNS13438 Class A EN 61000-4-2,3,4,5,6,8,11.... Breite: 40 mm, Tiefe: 113,5 mm, Höhe: 125,2 mm

Energie		Gewicht und Abmessungen	
Gesamtleistung *	120 W	Tiefe	113,5 mm
AC Eingangsspannung *	90 -264 V	Höhe	125,2 mm
AC Eingangsfrequenz	47 - 63 Hz	Gewicht	530 g
Eingangsstrom	2.25 A	Verpackungsdaten	
Haltezeit	16 ms	Verpackungsbreite	60 mm
Energieschutzeigenschaften	Überlastschutz, Überspannung, Kurzschluß	Verpackungstiefe	140 mm
Leistungen		Verpackungshöhe	143 mm
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	2636800 h	Paketgewicht	700 g
Design		Verpackungsart	Box
Produktfarbe	Blau, Silber	Logistikdaten	
Anzahl Lüfter	0 Lüfter	Anzahl Kartons pro Palette	20 Stück(e)
Betriebsbedingungen		Breite des Versandkartons	310 mm
Betriebstemperatur	-20 - 70 °C	Länge des Versandkartons	310 mm
Relative Luftfeuchtigkeit in Betrieb	0 - 90%	Höhe des Versandkartons	305 mm
Safety regulation & standards		Gewicht Versandkarton	14 kg
Sicherheit	EN 55032 (CISPR32) Class A EN 61000-3-2,-3,EACTPTC020,CNS13438 Class A EN 61000-4-2,3,4,5,6,8,11 EN 61204-3 EN 55035 EN 61000-6-2 (EN 50082-2) MTBF:2636.8K hrs min. Telcordia SR-332 (Bellcore)	Warentarifnummer (HS)	8504403090
		Ursprungsland	China
		Sonstige Funktionen	
		Spannungstoleranz	1%
		Ausgang Spannung (Note)	24V
		Stromstärke (maximal)	5 A
Gewicht und Abmessungen			
Breite	40 mm		



4015867236574

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-JUN-2026. Prints or copies of Information are only valid on the printed Publication date