TP-Link 5-Port 2.5G Desktop Switch

Marke : TP-Link

Artikel-Code: TL-SG105-M2

Produktname : 5-Port 2.5G Desktop Switch



5× 100Mbps/1Gbps/2.5Gbp, 25 Gbps, 18.6 Mpps, 16 K MAC, 1.5 Mb Buffer, 10 KB Jumbo, 209×126×26 TP-Link 5-Port 2.5G Desktop Switch. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: 2.5G Ethernet (100/1000/2500), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 5. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 25 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z



Management-Funktionen	
Switch-Typ *	Unmanaged
Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	5
Basic Switching RJ-45 Ethernet Ports-Typ *	2.5G Ethernet (100/1000/2500)
Anzahl 2.5G Ethernet (Kupfer)-Ports	5
Netzwerk	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G-Unterstützung *	✗
Auto MDI/MDI-X	✓
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
Auto-Negotiation-Funktion	✓
Datenübertragung	
Routing-/Switching-Kapazität *	25 Gbit/s
Transferrate	18,6 Mpps
MAC-Adressentabelle *	16000 Eintragungen
Store-and-Forward	✓
Jumbo Frames Unterstützung	✓
Jumbo-Frames	10000
Datenpaket-Pufferspeicher	1,5 MB
Design	
Rack-Einbau *	✗
Produktfarbe	Schwarz
LED-Anzeigen	✓
Energie	
Energiequelle *	Gleichstrom
Netzteil enthalten *	✓

Energie	
Eingangsstrom	1 A
Eingangsspannung	12 V
Stromverbrauch (max.)	12,11 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✗
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Luftfeuchtigkeit bei Lagerung	5 - 90%
Wärmeableitung	41,32 BTU/h
Gewicht und Abmessungen	
Breite	209 mm
Tiefe	126 mm
Höhe	26 mm
Lieferumfang	
Mitgelieferte Kabel	LAN (RJ-45)
Schnellstartübersicht	✓
Verpackungsdaten	
Verpackungsbreite	240 mm
Verpackungstiefe	315 mm
Verpackungshöhe	70 mm
Paketgewicht	920 g
Zertifikate	
Zertifizierung	CE, FCC ,RoHS
Logistikdaten	
Warentarifnummer (HS)	85176990



6935364052898



6935364052881



0845973089757



845973089757



1210002612654



1210002612661

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 29-OCT-2026. Prints or copies of Information are only valid on the printed Publication date