



D-Link DGS-1100-08PV2 Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz

Marke : D-Link

Artikel-Code: DGS-1100-08PV2/E

Produktname : DGS-1100-08PV2



8 x 10/100/1000 Mbps (PoE) RJ-45, 16 Gbps, 11.9 Mpps, 4K MAC, 171 x 97.8 x 28.6 mm
D-Link DGS-1100-08PV2. Switch-Typ: Managed, Switch-Ebene: L2/L3. Basic Switching RJ-45 Ethernet
Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8.
Vollduplex. MAC-Adressentabelle: 4096 Eintragungen, Routing-/Switching-Kapazität: 16 Gbit/s.
Netzstandard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE.... Power over Ethernet (PoE)

Management-Funktionen

Switch-Typ *	Managed
Switch-Ebene	L2/L3
Quality of Service (QoS) Support	✓
Web-basiertes Management	✓

Anschlüsse und Schnittstellen

Anzahl der basisschaltenden RJ-45 Ethernet Ports *	8
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Anzahl Gigabit Ethernet (Kupfer) Anschlüsse	8

Netzwerk

Netzstandard *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u
10G-Unterstützung *	✗
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T
Port-Spiegelung	✓
Vollduplex	✓
Halb-Duplex	✓
Unterstützung Datenflusssteuerung	✓
Link Aggregation	✓
Broadcast-Sturmkontrolle	✓
Auto MDI/MDI-X	✓
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
VLAN-Unterstützung	✓
Virtuelle LAN-Funktionen	Port-based VLAN, Tagged VLAN, Voice VLAN
Anzahl der VLANs	4094

Multicast-Funktionen

Multicast Unterstützung	✓
-------------------------	---

Design

Rack-Einbau *	✗
Produktfarbe	Schwarz
LED-Anzeigen	✓

Leistungen

Flash-Speicher	2 MB
Ventilatorlos	✓
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	786841 h

Energie

Netzteil enthalten *	✓
AC Eingangsspannung	100 - 240 V
Stromverbrauch (max.)	77,9 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✓
Anzahl Power over Ethernet plus (PoE+) Anschlüsse	8
Power over Ethernet (PoE) Leistung pro Anschluss	30 W
Gesamtleistung Power over Ethernet (PoE)	64 W

Betriebsbedingungen

Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 90%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Wärmeableitung	265,85 BTU/h

Gewicht und Abmessungen

Breite	171 mm
--------	--------

Datenübertragung		Gewicht und Abmessungen	
Routing-/Switching-Kapazität *	16 Gbit/s	Tiefe	97,8 mm
Transferrate	11,9 Mpps	Höhe	28,6 mm
MAC-Adressentabelle *	4096 Eintragungen	Gewicht	430 g
Anzahl Queues	4	Nachhaltigkeit	
Jumbo Frames Unterstützung	✓	Nachhaltigkeitskonformität	✓
Jumbo-Frames	9216	Zertifikate	
Sicherheit		Konformitätsbescheinigungen	CE, RoHS
IGMP-Snooping	✓	Zertifizierung	FCC Class B, CE Class B, VCCI Class B, BSMI cUL, CE LVD, CB, BSMI
Loop Protection	✓		
Warteschleifenplanungs-Algorithmen	SP, Weighted Round Robin (WRR)		



0790069467813



790069467813

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.