



FSP Clippers RT 1K Unterbrechungsfreie Stromversorgung (USV) Doppelwandler (Online) 1 kVA 1000 W



Marke : FSP

Artikel-Code: PPF10A0400

Produktname : Clippers RT 1K

FSP Clippers RT 1K. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 1 kVA, Ausgangsleistung: 1000 W. AC-Steckertypen: C13-Koppler, USB-Port-Typ: USB Typ-B, Serielle Schnittstelle: RS-232. Batteriekapazität: 9 Ah, Akku-/Batteriespannung: 12 V, Typische Backup-Zeit bei voller Belastung: 33 min. Formfaktor: Rackmount/Tower, Produktfarbe: Schwarz, Kühlung: Aktiv. Konformitätsbescheinigungen: CE, Zertifizierung: EMC EN62040-2 C2

Merkmale		Anschlüsse und Schnittstellen	
USV-Topologie *	Doppelwandler (Online)	Serielle Schnittstelle	✓
Ausgangskapazität *	1 kVA	Serielle Schnittstelle	RS-232
Ausgangsleistung *	1000 W	Notaus-Steckverbinder (EPO)	✓
Wellenform *	Sine	Akku/Batterie	
Eingangs-Betriebsspannung (min) *	110 V	Batteriekapazität	9 Ah
Eingangs-Betriebsspannung (max) *	300 V	Akku-/Batteriespannung	12 V
Eingangsfrequenz *	40/70 Hz	Anzahl Batteriezellen	2
Ausgangs-Betriebsspannung (min)	208 V	Typische Backup-Zeit bei voller Belastung	33 min
Ausgangs-Betriebsspannung (max)	240 V	Akkuladezeit	3 h
Output Frequenz	46/64 Hz	Hot-Swap-Batterie	✓
Regulierung der Ausgangsspannung	1%	Design	
Reaktionszeit	4 ms	Formfaktor *	Rackmount/Tower
Anzahl der Eingangs-Phasen	1	Kühlung	Aktiv
Leistungsfaktor	0,99	Eingebauter Ventilator	✓
Crest-Faktor	3:1	Produktfarbe *	Schwarz
Notstrom Aus (EPO)	✓	Steuerung	Tasten
Gesamtverzerrungsfaktor THD (lineare Last)	2%	Displaytyp	LCD
Gesamtverzerrungsfaktor THD (nichtlineare Last)	4%	Betriebsbedingungen	
Geräuschpegel	50 dB	Betriebstemperatur	0 - 40 °C
Druckanstiegsschutz	✓	Relative Luftfeuchtigkeit in Betrieb	20 - 90%
Akustische Signale	✓	Zertifikate	
Akustische Alarm-Modi	Alarm bei Batteriebetrieb, Störung, Warnung bei geringer Batterie, Überlastungsalarm	Konformitätsbescheinigungen	CE
Anschlüsse und Schnittstellen		Zertifizierung	EMC EN62040-2 C2
AC-Steckertypen	C13-Koppler	Nachhaltigkeit	
USB Anschluss	✓	Nachhaltigkeitskonformität	✓
Anzahl USB 2.0 Anschlüsse	1	Gewicht und Abmessungen	
USB-Port-Typ	USB Typ-B	Breite	438 mm
		Tiefe	410 mm
		Höhe	88 mm
		Gewicht	11,6 kg
		Logistikdaten	
		Warentarifnummer (HS)	85078000



4713224524882

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 29-OCT-2026. Prints or copies of Information are only valid on the printed Publication date