



TP-Link Omada EAP653 UR(EU) WLAN Access Point 2976 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: EAP653 UR(EU)

Produktname : EAP653 UR(EU)

TP-Link Omada EAP653 UR(EU). 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 2976 Mbit/s.
Unterstützte Sicherheitsalgorithmen: HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA, WPA2, WPA3. Ethernet
LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß

Merkmale		Sicherheit	
2,4 GHz *	✓	MAC Adressen Filtern	✓
5 GHz *	✓	Management-Funktionen	
6 GHz *	✗	Web-basiertes Management	✓
Maximale Datenübertragungsrate *	2976 Mbit/s	Syslog	✓
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s	Upgradefähige Firmware	✓
Maximale Datenübertragungsrate (5 GHz)	2402 Mbit/s	Anschlüsse und Schnittstellen	
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Frequenzband	2.4 - 5 GHz	Gleichstrom-Anschluss (DC)	✓
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11h	Energie	
Verkabelungstechnologie	10/100/1000Base-T(X)	Power over Ethernet (PoE) *	✓
Zahl der Benutzer	250 Benutzer	DC Spannungsbereich	12 V
Automatische Kanalwahl	✓	Design	
Automatischer Kanalscan	✓	Platzierung *	Zimmerdecke, Wand
MIMO	✓	Produktfarbe *	Weiß
MIMO-Typ	Multi User MIMO	Reset-Knopf	✓
Spread-Spectrum Methode	OFDMA	LED-Anzeigen	✓
AP-Modus-Eigenschaften anpassen	Vernetzung von Netzen	Antenne	
VLAN-Unterstützung	✓	Antennentyp *	Intern
Ratenbeschränkung	✓	Gewicht und Abmessungen	
Unterstützung Datenflusssteuerung	✓	Breite	160 mm
Bandsteuerung	✓	Tiefe	160 mm
Airtime Fairness (ATF)	✓	Höhe	33,6 mm
Quality of Service (QoS) Support	✓	Verpackungsdaten	
BeamForming	✓	Verpackungsart	Box
Sendeleistung (CE)	27 dbm	Lieferumfang	
Sendeleistung (FCC)	22 dbm	Menge pro Packung	1 Stück(e)
Sicherheit		Montageset	✓
Unterstützte Sicherheitsalgorithmen *	HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA, WPA2, WPA3	Schnellstartübersicht	✓
		Betriebsbedingungen	
		Relative Luftfeuchtigkeit in Betrieb	10 - 90%
		Betriebstemperatur	0 - 40 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.