



## TP-Link TL-SG105E(UN) Netzwerk-Switch Managed L2 Gigabit Ethernet (10/100/1000) Schwarz

Marke : TP-Link

Artikel-Code: TL-SG105E(UN)

Produktname : TL-SG105E(UN)

TP-Link TL-SG105E(UN). Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 5. MAC-Adressentabelle: 8192 Eintragungen. Netzstandard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. DC input Spannung: 5 V



| Management-Funktionen                              |                                                                              | Design                               |             |
|----------------------------------------------------|------------------------------------------------------------------------------|--------------------------------------|-------------|
| Switch-Typ *                                       | Managed                                                                      | Produktfarbe                         | Schwarz     |
| Switch-Ebene                                       | L2                                                                           | LED-Anzeigen                         | ✓           |
| Quality of Service (QoS) Support                   | ✓                                                                            | Energie                              |             |
| Web-basiertes Management                           | ✓                                                                            | Netzteil enthalten *                 | ✓           |
| Anschlüsse und Schnittstellen                      |                                                                              | AC Eingangsspannung                  | 220 V       |
| Anzahl der basisschaltenden RJ-45 Ethernet Ports * | 5                                                                            | AC Eingangsfrequenz                  | 50 Hz       |
| Basic Switching RJ-45 Ethernet Ports-Typ *         | Gigabit Ethernet (10/100/1000)                                               | DC input Spannung                    | 5 V         |
| Anzahl Gigabit Ethernet (Kupfer) Anschlüsse        | 5                                                                            | Eingangsstrom                        | 0.6 A       |
| Netzwerk                                           |                                                                              | Stromverbrauch (max.)                | 2,82 W      |
| Netzstandard *                                     | IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x | Power over Ethernet (PoE)            |             |
| 10G-Unterstützung *                                | ✗                                                                            | Power over Ethernet (PoE) *          | ✗           |
| Kupfer Ethernet Verkabelungstechnologie            | 10BASE-T, 100BASE-TX, 1000BASE-T                                             | Betriebsbedingungen                  |             |
| Port-Spiegelung                                    | ✓                                                                            | Betriebstemperatur                   | 0 - 40 °C   |
| Unterstützung Datenflusssteuerung                  | ✓                                                                            | Temperaturbereich bei Lagerung       | -40 - 70 °C |
| Link Aggregation                                   | ✓                                                                            | Relative Luftfeuchtigkeit in Betrieb | 10 - 90%    |
| Auto MDI/MDI-X                                     | ✓                                                                            | Luftfeuchtigkeit bei Lagerung        | 5 - 90%     |
| VLAN-Unterstützung                                 | ✓                                                                            | Wärmeableitung                       | 9,62 BTU/h  |
| Anzahl der VLANs                                   | 32                                                                           | Gewicht und Abmessungen              |             |
| Datenübertragung                                   |                                                                              | Breite                               | 100 mm      |
| Durchgang                                          | 7,4 Mpps                                                                     | Tiefe                                | 98 mm       |
| MAC-Adressentabelle *                              | 8192 Eintragungen                                                            | Höhe                                 | 25 mm       |
| Store-and-Forward                                  | ✓                                                                            | Lieferumfang                         |             |
|                                                    |                                                                              | Mitgelieferte Kabel                  | AC          |
|                                                    |                                                                              | Schnellstartübersicht                | ✓           |
|                                                    |                                                                              | Benutzerhandbuch                     | ✓           |
|                                                    |                                                                              | Rackmontageset                       | ✓           |

| Datenübertragung           |       | Verpackungsdaten      |               |
|----------------------------|-------|-----------------------|---------------|
| Jumbo Frames Unterstützung | ✓     | Verpackungsart        | Box           |
| Jumbo-Frames               | 16000 | Zertifikate           |               |
| Datenpaket-Pufferspeicher  | 1 MB  | Zertifizierung        | FCC, CE, RoHS |
| Sicherheit                 |       | Logistikdaten         |               |
| IGMP-Snooping              | ✓     | Warentarifnummer (HS) | 85176990      |
| Design                     |       |                       |               |
| Rack-Einbau *              | ✗     |                       |               |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.