ZYXEL

Zyxel GS1100-24ES Unmanaged Gigabit Ethernet (10/100/1000) Schwarz



Marke : Zyxel

Artikel-Code: GS1100-24ES-EU0101F

Produktname : GS1100-24ES

Zyxel GS1100-24ES. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 48 Gbit/s. Netzstandard: IEEE 802.3az, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1p. Rack-Einbau

Management-Funktionen	
Switch-Typ *	Unmanaged
Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Netzwerk	
Netzstandard *	IEEE 802.3az, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1p
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
Datenübertragung	
Routing-/Switching-Kapazität *	48 Gbit/s
Durchgang	23,8 Mpps
Transferrate	35,7 Mpps
MAC-Adressentabelle *	16000 Eintragungen
Jumbo Frames Unterstützung	✔
Jumbo-Frames	12
Datenpaket-Pufferspeicher	1 MB
Sicherheit	
Loop Protection	✔
Design	
Rack-Einbau *	✔
Produktfarbe	Schwarz
LED-Anzeigen	✔
Leistungen	
Flash-Speicher	2 MB
Plug & Play	✔
Ventilatorlos	✔
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1131995 h

Energie	
Energiequelle *	AC
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50/60 Hz
Stromverbrauch (Standardbetrieb)	3,38 W
Stromverbrauch (max.)	12,21 W
Druckanstiegsschutz	✔
Druckanstieg-Schutzspannung	2 kV
Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Luftfeuchtigkeit bei Lagerung	10 - 95%
Wärmeableitung	41,662 BTU/h
Gewicht und Abmessungen	
Breite	280 mm
Tiefe	126 mm
Höhe	44 mm
Gewicht	1,02 kg
Lieferumfang	
Mitgelieferte Kabel	AC
Rackmontageset	✔
Verpackungsdaten	
Verpackungsbreite	330 mm
Verpackungstiefe	254 mm
Verpackungshöhe	61,5 mm
Paketgewicht	1,83 kg
Zertifikate	
Konformitätsbescheinigungen	REACH, RoHS, BSMI, RCM, Eidgenössische Kommunikationskommission (FCC), CE, Niederspannungsrichtlinie (LVD)

4718937652754

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 09-NOV-2026. Prints or copies of Information are only valid on the printed Publication date