

NETGEAR MS308 Unmanaged 2.5G Ethernet (100/1000/2500) Schwarz

Marke : NETGEAR

Artikel-Code: MS308-100EUS

Produktname : MS308



NETGEAR MS308. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: 2.5G Ethernet (100/1000/2500), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. Vollduplex. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 40 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x. DC input Spannung: 12 V. Wandmontage

Management-Funktionen		Design	
Switch-Typ *	Unmanaged	Anzahl Lüfter	0 Lüfter
Quality of Service (QoS) Support	✓	Leistungen	
Anschlüsse und Schnittstellen		Geräuschpegel	0 dB
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	8	Ventilatorlos	✓
Basic Switching RJ-45 Ethernet Ports-Typ *	2.5G Ethernet (100/1000/2500)	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	3309911 h
Netzwerk		Energie	
Netzstandard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x	Energiequelle *	Gleichstrom
10G-Unterstützung *	✗	Netzteil enthalten *	✓
Vollduplex	✓	DC input Spannung	12 V
Halb-Duplex	✓	Eingangsstrom	1 A
Auto MDI/MDI-X	✓	Eingangsspannung	12 V
Head-of-Line (HOL)-Blocking	✓	Stromverbrauch (max.)	7,98 W
Ethernet LAN Datentransferraten	100,1000,2500 Mbit/s	Power over Ethernet (PoE)	
Kabellängenerfassung	✓	Power over Ethernet (PoE) *	✗
Datenübertragung		Sonstige Funktionen	
Routing-/Switching-Kapazität *	40 Gbit/s	Garantiezeit	3 Jahr(e)
Transferrate	3,72 Mpps	Betriebsbedingungen	
MAC-Adressentabelle *	16000 Eintragungen	Betriebstemperatur	0 - 40 °C
Wartezeit (1 Gbps)	4,9 µs	Temperaturbereich bei Lagerung	-20 - 70 °C
Jumbo Frames Unterstützung	✓	Relative Luftfeuchtigkeit in Betrieb	0 - 90%
Jumbo-Frames	12288	Luftfeuchtigkeit bei Lagerung	0 - 95%
Datenpaket-Pufferspeicher	1 MB	Höhe bei Betrieb	0 - 3000 m
Design		Gewicht und Abmessungen	
Rack-Einbau *	✗	Breite	158 mm
Stapelbar *	✗	Tiefe	101 mm
Produktfarbe	Schwarz	Höhe	27 mm
Gehäusematerial	Metall	Gewicht	430 g
LED-Anzeigen	✓	Zertifikate	
Wandmontage	✓	Konformitätsbescheinigungen	CCC, Niederspannungsrichtlinie (LVD)



0606449170788



606449170788

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.