



Cudy GS1016 Netzwerk-Switch Unmanaged Gigabit Ethernet (10/100/1000) Schwarz



Marke : Cudy

Artikel-Code: GS1016

Produktname : GS1016

- 16x GbE
- Standard-/VLAN-/Erweiterungsmodi
- Verlängerung um 250 Meter Übertragung
- VLAN für Client-Isolation
- Desktop, Rackmontage
- 200x118x44 mm (7,87x4,65x1,73")
- 617 g (21,76 oz.)

16 10/100/1000Mbps Auto Negotiation, Auto MDI/MDIX, RJ-45, Schwarz

Cudy GS1016. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 16. MAC-Adressentabelle: 8192 Eintragungen, Routing-/Switching-Kapazität: 32 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Netzstecker: AC-Eingangsbuchse. Rack-Einbau

Management-Funktionen		Design	
Switch-Typ *	Unmanaged	Produktfarbe	Schwarz
Anschlüsse und Schnittstellen		Energie	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	16	Energiequelle *	AC
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Netzteil enthalten *	✓
Anzahl Gigabit Ethernet (Kupfer) Anschlüsse	16	AC Eingangsspannung	90 - 260 V
Netzstecker	AC-Eingangsbuchse	AC Eingangsfrequenz	50/60 Hz
Netzwerk		Stromverbrauch (max.)	15 W
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Betriebsbedingungen	
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Betriebstemperatur	0 - 40 °C
unterstützte Kabeltypen	Cat3, Cat5, Cat5e	Temperaturbereich bei Lagerung	-40 - 70 °C
Unterstützung Datenflusssteuerung	✓	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Luftfeuchtigkeit bei Lagerung	5 - 90%
VLAN-Unterstützung	✓	Gewicht und Abmessungen	
Datenübertragung		Breite	118 mm
Routing-/Switching-Kapazität *	32 Gbit/s	Tiefe	200 mm
Transferrate	23,808 Mpps	Höhe	44 mm
MAC-Adressentabelle *	8192 Eintragungen	Lieferumfang	
Store-and-Forward	✓	Mitgelieferte Kabel	AC
Design		Betriebsanleitung	✓
Rack-Einbau *	✓	Verpackungsdaten	
		Verpackungsbreite	230 mm
		Verpackungstiefe	202 mm
		Verpackungshöhe	78 mm



6971690791117

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.