



Cudy POE400 PoE-Adapter Gigabit Ethernet 56 V

Marke : Cudy

Artikel-Code: POE400

Produktname : POE400

- GbE Eingang, GbE Ausgang
- 100 m (328 ft) Übertragungsdistanz
- 802.3bt/at/af, max. 90 W, 4-Paar
- Leistung, PoE-Wattzahl-LED
- Überspannungs-/ESD-Schutz

90W, Gigabit, PoE/PoE+/PoE++ Injector, Model: POE400, Black, Surge protection, Plug and play
Cudy POE400. Ethernet Schnittstellen Typ: Gigabit Ethernet, Ethernet LAN Datentransferraten:
10,100,1000 Mbit/s, Verkabelungstechnologie: 10/100/1000. Produktfarbe: Schwarz, Maximaler
Arbeitsabstand: 100 m, LED-Anzeigen: PoE, Leistung. Power over Ethernet (PoE) Spannung: 56 V,
Ausgangsleistung: 90 W, Netzteil Eingangsspannung: 100 - 240 V. Breite: 178,5 mm, Tiefe: 80 mm,
Höhe: 46 mm. Anzahl enthaltener Produkte: 1 Stück(e)



Netzwerk		Energie	
Ethernet Schnittstellen Typ	Gigabit Ethernet	Ausgangsleistung	90 W
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Netzteil Eingangsspannung	100 - 240 V
Verkabelungstechnologie	10/100/1000	Netzteilfrequenz	50 - 60 Hz
Power over Ethernet (PoE)	✓	Eingangsstrom	1 A
Netzstandard	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt	Betriebsbedingungen	
unterstützte Kabeltypen	Cat5e	Betriebstemperatur	-10 - 45 °C
Merkmale		Temperatur Betriebsumgebung	14 - 113 °F
Produktfarbe	Schwarz	Relative Luftfeuchtigkeit in Betrieb	10 - 80%
Wandmontage	✓	Temperaturbereich bei Lagerung	-20 - 70 °C
Plug & Play	✓	Luftfeuchtigkeit bei Lagerung	5 - 80%
Druckanstiegsschutz	✓	Gewicht und Abmessungen	
Maximaler Arbeitsabstand	100 m	Breite	178,5 mm
LED-Anzeigen	PoE, Leistung	Tiefe	80 mm
Pin-Zuordnung & Polarität	1/2 (-), 3/6 (+), 4/5 (+), 7/8 (-)	Höhe	46 mm
Energieschutzeigenschaften	Überstrom, Überspannung, Überlastschutz	Lieferumfang	
Anschlüsse und Schnittstellen		Anzahl enthaltener Produkte	1 Stück(e)
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	2	Netzkabel enthalten	✓
RJ-45-Eingangsanschlüsse	1	Verpackungsdaten	
RJ-45-Ausgangsanschlüsse	1	Verpackungsbreite	195 mm
Energie		Verpackungstiefe	138 mm
Power over Ethernet (PoE)	56 V	Verpackungshöhe	57 mm
Spannung *			



6971690791087

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.