



APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack-montierbar, NMC, 750VA

Marke : APC

Artikel-Code: SMT750RMI2UNC

Produktname : APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack-montierbar, NMC, 750VA



APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack-montierbar, NMC, 750VA

APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack-montierbar, NMC, 750VA. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 0,75 kVA, Ausgangsleistung: 500 W. AC-Steckertypen: C13-Koppler, C14-Koppler, Stecker: C14-Koppler, Anzahl der AC-Ausgänge: 4 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Batteriekapazität: 168 Ah, Akkuladezeit: 3 h. Formfaktor: Rackmount, Produktfarbe: Schwarz, Rack-Kapazität: 2U. Konformitätsbescheinigungen: RoHS, Zertifizierung: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE



Merkmale		Design	
USV-Topologie *	Line-Interaktiv	Formfaktor *	Rackmount
Ausgangskapazität *	0,75 kVA	Rack-Kapazität	2U
Ausgangsleistung *	500 W	Produktfarbe *	Schwarz
Wellenform *	Sine	Display-Typ	LCD
Eingangs-Betriebsspannung (min) *	151 V	LED-Anzeigen	✓
Eingangs-Betriebsspannung (max) *	302 V	Betriebsbedingungen	
Eingangsfrequenz *	50/60 Hz	Betriebstemperatur	0 - 40 °C
Ausgangs-Betriebsspannung (min)	220 V	Temperaturbereich bei Lagerung	-15 - 45 °C
Ausgangs-Betriebsspannung (max)	240 V	Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Output Frequenz	50/60 Hz	Luftfeuchtigkeit bei Lagerung	0 - 95%
Regulierung der Ausgangsfrequenz	+/- 3 Hz	Höhe bei Betrieb	0 - 3000 m
Regulierung der Ausgangsspannung	5%	Höhe bei Lagerung	0 - 15000 m
Anstieg der Energiemenge	459 J	Zertifikate	
Reaktionszeit	2 ms	Konformitätsbescheinigungen	RoHS
Notstrom Aus (EPO)	0	Zertifizierung	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Geräuschpegel	46 dB	Lieferumfang	
Druckanstiegsschutz	✓	Rackmontageset	✓
Akustische Signale	✓	Mitgelieferte Kabel	Eingangskabel, USB-Kabel
Web-basiertes Management	✓	Management-Karte enthalten	✓
Akustische Alarm-Modi	Batterieaustausch	Schnellinstallationsanleitung	✓
Auto-Neustart	✓	Nachhaltigkeit	
Anschlüsse und Schnittstellen		Nachhaltigkeitszertifikate	Green Premium
AC-Steckertypen	C13-Koppler, C14-Koppler	Gewicht und Abmessungen	
Stecker	C14-Koppler	Breite	432 mm
Anzahl der AC-Ausgänge	4 AC-Ausgänge	Tiefe	406 mm
Anzahl USB 2.0 Anschlüsse	1	Höhe	89 mm
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1	Gewicht	17,2 kg
SmartSlot	✓	Verpackungsdaten	
SmartConnect-Anschluss	✗	Ressourcen-CD	✓
Akku/Batterie		Verpackungsbreite	546 mm
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)	Verpackungstiefe	584 mm
Batteriekapazität	168 Ah	Verpackungshöhe	241 mm
Akkuladezeit	3 h		
Hot-Swap-Batterie	✓		

Akku/Batterie		Verpackungsdaten	
Automatischer Batterietest	✓	Paketgewicht	21,2 kg
Kaltstart	✓	Logistikdaten	
		Produkte pro Palette	16 Stück(e)
		Warentarifnummer (HS)	85078000
		Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	497,38
		Sonstige Funktionen	
		Ausgangsspannung	230 V



0731304327721



731304327721

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.