



## D-Link GO-SW-8G/E Netzwerk-Switch Unmanaged Gigabit Ethernet (10/100/1000) Weiß



**Marke :** D-Link

**Artikel-Code:** GO-SW-8G/E

**Produktname :** GO-SW-8G/E

8 x 10/100/1000BASE-T Gigabit LAN, MAC 4K, Jumbo frame, 130 x 79 x 22 mm

D-Link GO-SW-8G/E. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. Vollduplex. MAC-Adressentabelle: 8000 Eintragungen, Routing-/Switching-Kapazität: 16 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Netzstecker: DC-Anschluss

| Management-Funktionen                              |                                                                  | Betriebsbedingungen                   |               |
|----------------------------------------------------|------------------------------------------------------------------|---------------------------------------|---------------|
| Switch-Typ *                                       | Unmanaged                                                        | Betriebstemperatur                    | 0 - 40 °C     |
| Anschlüsse und Schnittstellen                      |                                                                  | Temperaturbereich bei Lagerung        | -10 - 70 °C   |
| Anzahl der basisschaltenden RJ-45 Ethernet Ports * | 8                                                                | Relative Luftfeuchtigkeit in Betrieb  | 10 - 90%      |
| Basic Switching RJ-45 Ethernet Ports-Typ *         | Gigabit Ethernet (10/100/1000)                                   | Luftfeuchtigkeit bei Lagerung         | 5 - 90%       |
| Netzwerk                                           |                                                                  | Gewicht und Abmessungen               |               |
| Anzahl Gigabit Ethernet (Kupfer) Anschlüsse        | 8                                                                | Breite                                | 128 mm        |
| Netzstecker                                        | DC-Anschluss                                                     | Tiefe                                 | 68,5 mm       |
|                                                    |                                                                  | Höhe                                  | 25,4 mm       |
|                                                    |                                                                  | Gewicht                               | 195 g         |
| Netzwerk                                           |                                                                  | Lieferumfang                          |               |
| Netzstandard *                                     | IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Benutzerhandbuch                      | ✓             |
| 10G-Unterstützung *                                | ✗                                                                | Verpackungsdaten                      |               |
| Kupfer Ethernet Verkabelungstechnologie            | 1000BASE-T, 100BASE-TX, 10BASE-T                                 | AC-Netzadapter                        | ✓             |
| Vollduplex                                         | ✓                                                                | Verpackungsbreite                     | 104 mm        |
| Unterstützung Datenflusssteuerung                  | ✓                                                                | Verpackungstiefe                      | 158 mm        |
| Auto MDI/MDI-X                                     | ✓                                                                | Verpackungshöhe                       | 94 mm         |
| Selbstlernen von MAC-Adressen unterstützt          | ✓                                                                | Paketgewicht                          | 281 g         |
| Datenübertragung                                   |                                                                  | Technische Details                    |               |
| Routing-/Switching-Kapazität *                     | 16 Gbit/s                                                        | Versandkartonshöhe                    | 19,3 cm       |
| MAC-Adressentabelle *                              | 8000 Eintragungen                                                | Versandkartonsbreite                  | 23 cm         |
| Store-and-Forward                                  | ✓                                                                | Versandkartonslänge                   | 49,8 cm       |
| Jumbo Frames Unterstützung                         | ✓                                                                | Nettogewicht Versandkarton            | 1,95 kg       |
| Jumbo-Frames                                       | 9216                                                             | Menge pro Versandkarton               | 10 Stück(e)   |
| Paketweiterleitungsrate (1 Gbit/s)                 | 1488000 pps                                                      | Palettenbruttogewicht (Luft)          | 348,5 kg      |
| Paketweiterleitungsrate (100 Mbit/s)               | 148800 pps                                                       | Anzahl der Kartons pro Palette (Luft) | 100 Stück(e)  |
| Paketweiterleitungsrate (10 Mbit/s)                | 14880 pps                                                        | Anzahl pro Palette (Luft)             | 1000 Stück(e) |
| Protokolle                                         |                                                                  | Palettenlänge (brutto)                | 110 cm        |
| Unterstützte Netzwerkprotokolle                    | CSMA/CD                                                          | Palettenbreite (brutto)               | 120 cm        |
| Design                                             |                                                                  | Palettenhöhe (Luft)                   | 2,06 m        |
| Rack-Einbau *                                      | ✗                                                                | Palettenbruttogewicht (Meer)          | 348,5 kg      |
| Produktfarbe                                       | Weiß                                                             | Anzahl der Kartons pro Palette (See)  | 100 Stück(e)  |
| LED-Anzeigen                                       | ✓                                                                | Anzahl pro Palette (See)              | 1000 Stück(e) |
|                                                    |                                                                  | Palettenhöhe (See)                    | 2,06 m        |
|                                                    |                                                                  | Gewicht (innerer) Versandkarton       | 3,3 kg        |

| Leistungen                                       |          | Zertifikate           |                                   |
|--------------------------------------------------|----------|-----------------------|-----------------------------------|
| Puffergröße                                      | 128 KB   | Zertifizierung        | FCC cUL/UL ICES-003 CCC CE Anatel |
| Mittlere Betriebsdauer zwischen Ausfällen (MTBF) | 412433 h |                       | C-Tick LVD VCCI                   |
| Energie                                          |          | Logistikdaten         |                                   |
| Ausgangsspannung                                 | 5 V      | Warentarifnummer (HS) | 85176990                          |
| Ausgangsstrom                                    | 1 A      |                       |                                   |



7900693656900



0790069365690



790069365690



4052305795910

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.