



D-Link DGS-1100-18PV2 Netzwerk-Switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Schwarz

Marke : D-Link

Artikel-Code: DGS-1100-18PV2

Produktname : DGS-1100-18PV2

D-Link DGS-1100-18PV2. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 16. Vollduplex. Routing-/Switching-Kapazität: 36 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u,.... Power over Ethernet (PoE). Rack-Einbau, Formfaktor: 1U



Management-Funktionen		Design	
Switch-Typ *	Managed	Formfaktor	1U
Switch-Ebene	L2	Produktfarbe	Schwarz
Quality of Service (QoS) Support	✓	Anzahl Lüfter	1 Lüfter
Anschlüsse und Schnittstellen		Elektromagnetische Verträglichkeit	FCC Class A, CE Class A, VCCI Class A, C-Tick, BSMI
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	16	Leistungen	
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Geräuschpegel	45,8 dB
Anzahl Combo-SPF-Anschlüsse	2	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	343695 h
Netzwerk		Energie	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x	Energiequelle *	DC/PoE
10G-Unterstützung *	✗	Netzteil enthalten *	✓
Kupfer Ethernet Verkabelungstechnologie	1000BASE-T	AC Eingangsspannung	100 - 240 V
Vollduplex	✓	AC Eingangsfrequenz	50 - 60 Hz
Halb-Duplex	✓	Power over Ethernet (PoE)	
Unterstützung Datenflusssteuerung	✓	Power over Ethernet (PoE) *	✓
Link Aggregation	✓	Anzahl Power over Ethernet (PoE) Anschlüsse	16
Auto MDI/MDI-X	✓	Gesamtleistung Power over Ethernet (PoE)	130 W
Spannbaum-Protokoll	✓	Betriebsbedingungen	
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Betriebstemperatur	-5 - 50 °C
Auto-Negotiation-Funktion	✓	Temperaturbereich bei Lagerung	-40 - 70 °C
VLAN-Unterstützung	✓	Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Anzahl der VLANs	4094	Luftfeuchtigkeit bei Lagerung	0 - 95%
Datenübertragung	Routing-/Switching-Kapazität *	Wärmeableitung	125,2 BTU/h
		Gewicht und Abmessungen	
		Breite	280 mm
		Tiefe	230 mm
Transferrate	26,78 Mpps	Höhe	44 mm
Jumbo Frames Unterstützung	✓	Gewicht	2,1 kg
Jumbo-Frames	9216	Zertifikate	
Sicherheit		Konformitätsbescheinigungen	RoHS
IGMP-Snooping	✓	Zertifizierung	cUL, UL, LVD, CB, BSMI

Design

Rack-Einbau * 



0790069453366



790069453366

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.