



## TP-Link UH9120C Schnittstellen-Hub USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s

**Marke :** TP-Link

**Artikel-Code:** UH9120C

**Produktname :** UH9120C

USB Type-C 9 in 1 Hub

TP-Link UH9120C. Hostschnittstelle: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Hub-Schnittstellen: HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Kompatible Speicherkarten: MicroSD (TransFlash), SD. Datenübertragungsrate: 5000 Mbit/s, Zertifizierung: CE, FCC, RoHS, HDMI, BSMI. Unterstützung anderer Betriebssysteme: Android, ChromeOS, iOS. Breite: 140,2 mm, Tiefe: 43 mm, Höhe: 14,3 mm. Verpackungsbreite: 190 mm, Verpackungstiefe: 90 mm, Verpackungshöhe: 20 mm



| Anschlüsse und Schnittstellen                             |                                                                                 | Systemanforderung                     |                        |
|-----------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------|------------------------|
| Hostschnittstelle *                                       | USB 3.2 Gen 1 (3.1 Gen 1) Type-C                                                | Unterstützte Linux-Betriebssysteme    | ✓                      |
| Hub-Schnittstellen *                                      | HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C | Unterstützung anderer Betriebssysteme | Android, ChromeOS, iOS |
| USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ A | 1                                                                               | <b>Gewicht und Abmessungen</b>        |                        |
| USB 3.2 Gen 1 (3.1 Gen 1) Anzahl der Anschlüsse vom Typ C | 3                                                                               | Breite                                | 140,2 mm               |
| Anzahl HDMI-Anschlüsse                                    | 1                                                                               | Tiefe                                 | 43 mm                  |
| Anzahl Anschlüsse *                                       | 9                                                                               | Höhe                                  | 14,3 mm                |
| Integrierter Kartenleser                                  | ✓                                                                               | <b>Verpackungsdaten</b>               |                        |
| Kompatible Speicherkarten                                 | MicroSD (TransFlash), SD                                                        | Verpackungsbreite                     | 190 mm                 |
| <b>Merkmale</b>                                           |                                                                                 | Verpackungstiefe                      | 90 mm                  |
| Datenübertragungsrate *                                   | 5000 Mbit/s                                                                     | Verpackungshöhe                       | 20 mm                  |
| Zertifizierung                                            | CE, FCC, RoHS, HDMI, BSMI                                                       | Paketgewicht                          | 140 g                  |
| <b>Systemanforderung</b>                                  |                                                                                 | <b>Betriebsbedingungen</b>            |                        |
| Unterstützt Windows-Betriebssysteme                       | ✓                                                                               | Betriebstemperatur                    | 0 - 40 °C              |
| Unterstützt Mac-Betriebssysteme                           | ✓                                                                               | Relative Luftfeuchtigkeit in Betrieb  | 10 - 90%               |
|                                                           |                                                                                 | Luftfeuchtigkeit bei Lagerung         | 5 - 90%                |



8885020625325



8885021371900



8885020625318

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.