



TP-Link Omada SG3210XHP-M2 Managed L2+ 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) 1U Schwarz

Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: SG3210XHP-M2(UN)

Produktname : SG3210XHP-M2



TP-Link Omada SG3210XHP-M2. Switch-Typ: Managed, Switch-Ebene: L2+. Basic Switching RJ-45 Ethernet Ports-Typ: 2.5G Ethernet (100/1000/2500), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 80 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1s, IEEE 802.1w. Netzstecker: AC-Eingangsbuchse. Power over Ethernet (PoE). Rack-Einbau, Formfaktor: 1U



Management-Funktionen		Sicherheit	
Switch-Typ *	Managed	SSH-/SSL-Unterstützung	✓
Switch-Ebene	L2+	Loop Protection	✓
Quality of Service (QoS) Support	✓	BPDU-Filterung/Schutz	✓
Web-basiertes Management	✓	IP-MAC-Portbindung	✓
Cloud-verwaltet	✓	Authentifizierung	MAC-basierte Authentifizierung, Port-basierte Authentifizierung
Traffic-Klassifizierung	✓	Passwortschutz	✓
ARP-Inspektion	✓	Autentifizierungstyp	AAA, TACACS+
Konfiguration der Standorteinstellungen (CLI)	✓	Warteschleifenplanungs-Algorithmen	SP, WRR+SP, Weighted Round Robin (WRR)
Systemereignisprotokoll	✓	Multicast-Funktionen	
MIB Unterstützung	RFC2925, RFC2618, RFC2620, RFC2021, RFC2819, RFC2674, RFC1493, RFC1643, RFC2233, RFC1213	Multicast Unterstützung	✓
Anschlüsse und Schnittstellen		Multicast Listener Discovery (MLD) Snooping	✓
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	8	Protokolle	
Basic Switching RJ-45 Ethernet Ports-Typ *	2.5G Ethernet (100/1000/2500)	Management-Protokolle	SNMPv1/v2c/v3, SNMP
Anzahl 2.5G Ethernet (Kupfer)-Ports	8	GARP VLAN Registration Protocol (GVRP)	✓
Menge Modul-Steckplätze SFP+	2	Design	
Netzstecker	AC-Eingangsbuchse	Rack-Einbau *	✓
Netzwerk		Formfaktor	1U
Netzstandard *	IEEE 802.1D, IEEE 802.1s, IEEE 802.1w	Produktfarbe	Schwarz
10G-Unterstützung *	✓	LED-Anzeigen	✓
Port-Spiegelung	✓	Anzahl Lüfter	2 Lüfter
IP-Routing	✓	Energie	
		Energiequelle *	AC
		Netzteil enthalten *	✓

Netzwerk		Energie	
Unterstützung Datenflusssteuerung	✓	AC Eingangsspannung	100 - 240 V
Link Aggregation	✓	AC Eingangsfrequenz	50/60 Hz
Broadcast-Sturmkontrolle	✓	Stromverbrauch (max.)	285,9 W
Ratenbeschränkung	✓	Power over Ethernet (PoE)	
Spannbaum-Protokoll	✓	Power over Ethernet (PoE) *	✓
Head-of-Line (HOL)-Blocking	✓	Anzahl Power over Ethernet plus (PoE+) Anschlüsse	8
Ethernet LAN Datentransferraten	100,1000,2500 Mbit/s	Power over Ethernet (PoE) Leistung pro Anschluss	30 W
VLAN-Unterstützung	✓	Gesamtleistung Power over Ethernet (PoE)	240 W
Virtuelle LAN-Funktionen	MAC address-based VLAN, Port-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN	Betriebsbedingungen	
Anzahl der VLANs	4000	Betriebstemperatur	0 - 45 °C
Datenübertragung		Temperaturbereich bei Lagerung	-40 - 70 °C
Routing-/Switching-Kapazität *	80 Gbit/s	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Transferrate	59,52 Mpps	Luftfeuchtigkeit bei Lagerung	5 - 90%
MAC-Adressentabelle *	16000 Eintragungen	Wärmeableitung	975,54 BTU/h
Statische Route	✓	Gewicht und Abmessungen	
Anzahl der statischen Routen	48	Breite	440 mm
Anzahl IP-Schnittstellen	16	Tiefe	180 mm
Jumbo Frames Unterstützung	✓	Höhe	44 mm
Jumbo-Frames	9000	Lieferumfang	
Datenpaket-Pufferspeicher	12 MB	Mitgelieferte Kabel	AC
Sicherheit		Schnellstartübersicht	✓
DHCP-Funktionen	DHCP client, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping	Verpackungsdaten	
Zugriffkontrollliste	✓	Verpackungsart	Box
IGMP-Snooping	✓	Zertifikate	
Unterstützte Sicherheitsalgorithmen	HTTPS, SSH, SSH-2, SSL/TLS	Zertifizierung	CE, FCC, RoHS
MAC Adressen Filtern	✓		
Statische Anschlusssicherheit	✓		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.