InLine HDMI AOC Kabel, Ultra High Speed HDMI Kabel, 8K4K, schwarz, 25m

Marke : InLine

Artikel-Code: 17925I

Produktname : InLine HDMI AOC Kabel, Ultra High Speed HDMI Kabel, 8K4K, schwarz, 25m

- Ultra HDMI 2.1 AOC Anschlusskabel
- Hybrid Kabel bestehend aus 4 Glasfaser- und 7 Vollkupferlitzen
- Richtungsgebundenes Signalkabel: HDMI Stecker (Quelle) an HDMI Stecker (Display)
- Robuste Metallstecker, Aramid-geschütztes und PVC-ummanteltes Kabel, schwarz
- Max. Datenübertragungsrate: 48 Gb/s (12 Gb/s pro Kanal)
- Unterstützte Auflösungen: UHD-II 7680x4320/8K@60Hz - UHD-I 3840x2160/4K@120Hz 4:4:4 8/10-Bit
- Mit DSC (Display Stream Compression) werden auch Auflösungen bis 8K@120Hz und 10K@100Hz unterstützt, vorausgesetzt die Geräte zur Wiedergabe und Empfang unterstützen diese Funktion.
- Unterstützt 3D, HDCP, EDID, CEC, DDC, Dynamic HDR, ARC und weitere Spezifikationen gemäß HDMI. eARC wird bis zu einer maximalen Kabellänge von 75 m unterstützt.
- Vergoldete Kontakte
- Kabeldurchmesser nur 4.8mm
- Betriebstemperatur: 0°C bis +50°C
- Lagertemperatur: -20°C bis +70°C

InLine HDMI AOC Kabel, Ultra High Speed HDMI, 8K4K, schwarz, 25 m

Merkmale	
Kabellänge *	25 m
Anschluss 1 *	HDMI Typ A (Standard)
Anschluss 2 *	HDMI Typ A (Standard)
Steckverbinder 1 Geschlecht *	Stecker
Steckverbinder 2 Geschlecht *	Stecker
Anschluss1 Formfaktor	Gerade
Anschluss2 Formfaktor	Gerade
Produktfarbe *	Schwarz
HDMI-Version	2.1
3D	✔
Unterstützte Grafik-Auflösungen	7680 x 4320
Audio Return Channel (ARC)	✔
HDCP	✔
Datenübertragungsrate	48 Gbit/s
High Dynamic Range Video (HDR) Unterstützung	✔
Unidirektional	✔
Maximale Bildwiederholrate	60 Hz
Beschichtung Steckerkontakte *	Gold

Merkmale	
Kabelmantelmaterial	Thermoplastische Polyurethane (TPU)
Betriebsbedingungen	
Betriebstemperatur	0 - 50 °C
Temperaturbereich bei Lagerung	-20 - 70 °C
Gewicht und Abmessungen	
Kabeldurchmesser	4,8 mm
Gewicht	643 g
Verpackungsvolumen	3200 cm³
Verpackungsdaten	
Verpackungsbreite	210 mm
Verpackungstiefe	218 mm
Verpackungshöhe	70 mm
Paketgewicht	753 g
Verpackungsart	Box
Sonstige Funktionen	
Tiefe	25000 mm
Höhe	10 mm
Breite	20 mm
Abmessungen (BxTxH)	20 x 25000 x 10 mm

4043718293568

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 14-OCT-2026. Prints or copies of Information are only valid on the printed Publication date