InLine USB4 Kabel, USB-C einseitig gewinkelt, PD 240W 8K60Hz, TPE schwarz, 0,5m

Marke : InLine

Artikel-Code: 35916I

Produktname : InLine USB4 Kabel, USB-C einseitig gewinkelt, PD 240W 8K60Hz, TPE schwarz, 0,5m

- Hochwertiges USB4-Kabel mit E-Marker: Strom-, Daten- und Bildübertragung
- Unterstützt die Spezifikation USB4 Gen.3x2 mit Datenübertragungen bis 40 Gb/s
- Unterstützt Auflösungen bis Ultra HD 8K@60Hz
- Unterstützt Power Delivery 3.1 Schnellladung bis max. 240 W (48 V/5 A)
- Kompatibel zu Thunderbolt 3
- Abwärtskompatibel zu USB 3.2 und USB 2.0
- USB-C Stecker auf USB-C Stecker
- Flexibles Kabel mit TPE-Mantel
- Hochwertige Verarbeitung mit verdrillten Adernpaaren
- Angespritzte Stecker mit langem Knickschutz für mehr Flexibilität und eine lange Haltbarkeit

InLine USB4 Kabel, USB-C, gewinkelt, PD 240 W, 8K60Hz, TPE, schwarz, 0,50 m
InLine USB4 Kabel, USB-C einseitig gewinkelt, PD 240W 8K60Hz, TPE schwarz, 0,5m. Kabellänge: 0,5 m. Anschluss 1: USB C, Anschluss 2: USB C, USB-Version: USB4 Gen 3x2, Max. Datenübertragungsrate: 40 Gbit/s, Produktfarbe: Schwarz

Merkmale	
USB-Version *	USB4 Gen 3x2
Anschluss 1 *	USB C
Anschluss 2 *	USB C
Steckverbinder 1 Geschlecht *	Stecker
Steckverbinder 2 Geschlecht *	Stecker
Anschluss1 Formfaktor	Gerade
Anschluss2 Formfaktor	Abgewinkelt
AWG Kabelgröße	24/32
Kabelmantelmaterial	Thermoplastisches Elastomer (TPE)
Art der Kabelummantelung	Extrem flexibel
Abschirmung Steckverbinder	✔
Maximale Datenübertragungsrate	40000 Mbit/s
Max. Datenübertragungsrate	40 Gbit/s
Kabeltyp	Rundkabel
Schnellladung	✔
USB Power Delivery	✔
USB-Stromversorgung Revision	3.1
USB-Stromversorgung bis zu	240 W
Produktfarbe *	Schwarz
Maximale Auflösung	7680 x 4320 Pixel
Thunderbolt-Technologie	✔
Thunderbolt-Version	4

Energie	
Ausgangsspannung	48 V
Outputstrom (max.)	5 A
Gewicht und Abmessungen	
Kabellänge *	0,5 m
Kabeldurchmesser	5,2 mm
Breite	21 mm
Tiefe	500 mm
Höhe	6 mm
Gewicht	27 g
Abmessungen (BxTxH)	21 x 500 x 6 mm
Verpackungsdaten	
Verpackungsart	Karton mit Aufhänger
Verpackungsbreite	105 mm
Verpackungstiefe	205 mm
Verpackungshöhe	21 mm
Paketgewicht	53 g
Lieferumfang	
Menge pro Packung *	1 Stück(e)
Nachhaltigkeit	
Nachhaltigkeitskonformität	✔
Zertifikate	
Konformitätsbescheinigungen	cTUVus
Logistikdaten	
Ursprungsland	China

4043718316816

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 14-OCT-2026. Prints or copies of Information are only valid on the printed Publication date