



InLine 66659E Netzwerk Medienkonverter 10000 Mbit/s 850 nm Multi-Modus Schwarz

Marke : InLine

Artikel-Code: 66659E

Produktname : 66659E

- Effizienter Medienkonverter zur einfachen Netzwerk-Migration von Kupfer auf Glasfaser
- Unterstützt 10 Gb/s Übertragungsrate für hohe Netzwerkperformance
- Link Fault Pass Through (LFP)-Funktion zur einfachen Wartung
- Geringer Stromverbrauch und stabile Performance über lange Zeiträume
- Plug-and-Play-Lösung für einfache Installation

Netzwerk Media Konverter 10Gb/s TP zu SFP+ LWL (für LC Duplex), MM, 300m

InLine 66659E. Maximale Datenübertragungsrate: 10000 Mbit/s, Converter Eingangsschnittstelle: 10Base-T, 10GBase-T, 100Base-T, 1000Base-T, Converter output Oberfläche: 10GBASE-R. Maximal mögliche Übertragungsstrecke: 300 m, Wellenlänge: 850 nm, Kabel mode struktur: Multi-Modus. LED-Anzeigen: Status, Produktfarbe: Schwarz. Optischer Kabelverbinder: LCD, SFP+, Übertragungstechnik: Kabelgebunden. Ausgangsspannung: 12 V, Ausgangsstrom: 1 A



Netzwerk		Energie	
Maximale Datenübertragungsrate *	10000 Mbit/s	Ausgangsstrom	1 A
Converter Eingangsschnittstelle	10Base-T, 10GBase-T, 100Base-T, 1000Base-T	Gewicht und Abmessungen	
Converter output Oberfläche	10GBASE-R	Breite	94 mm
Netzstandard	IEEE 802.3x	Tiefe	110 mm
Ethernet Schnittstellen Typ	2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Schnelles Ethernet, Gigabit Ethernet	Höhe	26 mm
Ethernet LAN Datentransferraten	10,100,1000,2500,5000,10000 Mbit/s	Gewicht	290 g
Link Fault Pass-Through (LFP)	✓	Betriebsbedingungen	
Leistungen		Betriebstemperatur	0 - 55 °C
Maximal mögliche Übertragungsstrecke *	300 m	Temperaturbereich bei Lagerung	-40 - 80 °C
Wellenlänge *	850 nm	Relative Luftfeuchtigkeit in Betrieb	5 - 80%
Kabel mode struktur	Multi-Modus	Lieferumfang	
Merkmale		AC-Netzadapter	✓
Eingebaut *	✗	Betriebsanleitung	✓
LED-Anzeigen	Status	Verpackungsdaten	
Produktfarbe	Schwarz	Verpackungsbreite	124 mm
Anschlüsse und Schnittstellen		Verpackungstiefe	230 mm
Übertragungstechnik	Kabelgebunden	Verpackungshöhe	52 mm
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1	Verpackungsvolumen	1400 cm³
Anzahl Faseranschlüsse	1	Paketgewicht	388 g
Optischer Kabelverbinder *	LCD, SFP+	Verpackungsart	Box
Energie		Zertifikate	
Ausgangsspannung	12 V	Konformitätsbescheinigungen	TÜV mark
		Logistikdaten	
		Ursprungsland	Taiwan

Sonstige Funktionen

Abmessungen (BxTxH)

94 x 110 x 26 mm



4043718338047

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.