



InLine Schnittstellenkarte, 2x Seriell 9-pol, PCIe (PCI-Express)

Marke : InLine

Artikel-Code: 76619D

Produktname : Schnittstellenkarte, 2x Seriell 9-pol, PCIe (PCI-Express)

InLine Schnittstellenkarte, 2x Seriell RS-232, PCIe, AX99100, Low-Profile

InLine Schnittstellenkarte, 2x Seriell 9-pol, PCIe (PCI-Express). Hostschnittstelle: PCIe, Ausgangsschnittstelle: Seriell, Geschlecht der Host-Schnittstelle: Männlich. Ursprungsland: China. Unterstützt Windows-Betriebssysteme: Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP, Unterstützte Linux-Betriebssysteme: Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4,..., Unterstützte Server-Betriebssysteme: Windows Server 2003, Windows Server 2007, Windows Server 2008, Windows Server 2012, Windows Server.... Breite: 120 mm, Tiefe: 1,24 mm, Höhe: 75 mm. Verpackungsbreite: 140 mm, Verpackungstiefe: 150 mm, Verpackungshöhe: 30 mm



Anschlüsse und Schnittstellen		Systemanforderung	
Hostschnittstelle *	PCIe	Unterstützte Linux-Betriebssysteme	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33, Kernel 3.12, Kernel 3.17, Kernel 3.3, Kernel 4.6.4, Linux Kernel 5.10, Linux Kernel 5.11, Linux Kernel 5.12, Linux Kernel 5.13, Linux Kernel 5.14, Linux Kernel 5.15, Linux Kernel 5.19, Linux Kernel 5.4, Linux Kernel 5.8, Linux Kernel 5.9, Linux Kernel 6.2
Geschlecht der Host-Schnittstelle	Männlich		Windows Server 2003, Windows Server 2007, Windows Server 2008, Windows Server 2012, Windows Server 2013, Windows Server 2016, Windows Server 2019, Windows Server 2022
Ausgangsschnittstelle *	Seriell		
Erweiterungskarte Standard	PCIe 2.0		
Anzahl serielle Anschlüsse	2		
Serielle Schnittstelle	RS-232, 9-polig		
Design		Unterstützte Server-Betriebssysteme	
Eingebaut *	✓		
Ursprungsland	China		
Energie		Gewicht und Abmessungen	
Stromversorgungsfunktionen - Beschreibung	✓	Breite	120 mm
Systemanforderung		Tiefe	1,24 mm
Unterstützt Windows-Betriebssysteme	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP	Höhe	75 mm
		Gewicht	2,5 kg
		Verpackungsdaten	
		Verpackungsbreite	140 mm
		Verpackungstiefe	150 mm
		Verpackungshöhe	30 mm
		Paketgewicht	46 g
		Verpackungsvolumen	1000 cm³
		Sonstige Funktionen	
		Abmessungen (BxTxH)	120 x 1,24 x 75 mm



4043718333202

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.