


INLINE® LWL DUPLEX KABEL, LC/ST, 50/125 M, OM3



- Duplex Glasfaser Patchkabel (LWL / Lichtwellenleiter)
- Faser: OM3 Multimode 50/125µm, halogenfrei LSZH
- Durchmesser 2.0mm (x2)
- 2x LC Stecker auf 2x ST Stecker
- Faserfarbe: Türkis
- in Shopwand-Tüte mit EAN Code

TEST VALUES					
	Allow Loss	Conn. 1	Conn. 2	Conn. 1	Conn. 2
Insertion Loss	0.30dB	dB	dB	dB	dB
Return Loss (VM)	NA	NA	NA	NA	NA
RESULT	OK				



⑦	Fiber Optical Cable Duplex Ø3.0 OM3 50/125um Aqua LSZH	L
⑥	Black Heat shrink tubing	2
⑤	ST 3.0 Red boot	1
④	ST 3.0 Black boot	1
③	ST MM Connector	2
②	ST/UPC MM Ferrule Ø126-128um	2
①	Transparent Dust cap	2

⑭	LC White Dust cap	2
⑬	LC/UPC MM Ferrule Ø126-128um	2
⑫	LC 3.0 MM Beige Simplex Connector	2
⑪	LC Beige Clip	1
⑩	LC White Boot	2
⑨	Ring (1)	2
⑧	Ring (2)	2

Art. Nr.	Länge	EAN
885040	0,50 m	4043718248612
885010	1 m	4043718166862
885020	2 m	4043718166879
885030	3 m	4043718125272
885050	5 m	4043718166886
885070	7,50 m	4043718248629
885100	10 m	4043718166893
885150	15 m	4043718248636
885200	20 m	4043718248643
885180	25 m	4043718248650

Note:
ROHS 2.0 and REACH Compliant

Type	Multi Mode
Insertion Loss	≤0.3dB
Return Loss	NA
Test Wavelength	850nm