



FSP Twins PRO 500W Netzteil PS2 ATX Redundant ATX Schwarz

Marke : FSP

Artikel-Code: PPA5008601

Produktname : Twins PRO 500W Netzteil PS2 ATX Redundant ATX Schwarz

- Entwickelt für ATX oder PS2 -Gehäuse
- Wirkungsgrad $\geq 90\%$ bei typischer Belastung
- Leiser und langlebiger kugelgelagerter 40-mm-Lüfter
- Inklusive Flachbandkabel, eine ideale Lösung um Platz im Gehäuse zu sparen
- Leistungsstarkes +12V-Single-Rail Design
- Japanische Elektrolytkondensatoren
- Bereit für aktuelle CPU Generationen
- Vollständiger Schutz OCP, OVP, SCP, OPP, OTP, FFP, UVP

500W, PS2 ATX Redundant, 80+ Gold, OCP, OVP, SCP, OPP, OTP, FFP, UVP, 40mm

FSP Twins PRO 500W Netzteil PS2 ATX Redundant ATX Schwarz. Gesamtleistung: 500 W, AC Eingangsspannung: 100 - 240 V, AC Eingangsfrequenz: 50 - 60 Hz. Motherboard Anschlussstecker: 20+4 pin ATX, Kabeltyp: Nicht-modular. Zweck: Server, Stromversorgungseinheit (PSU) Formfaktor: PS/2, 80 Plus Zertifizierung: 80 PLUS Gold. Produktfarbe: Schwarz, Lüfterdurchmesser: 4 cm, Anzahl Lüfter: 2 Lüfter. Mitgelieferte Kabel: CPU, PCIe, SATA



Energie		Anschlüsse und Schnittstellen	
Gesamtleistung *	500 W	Anzahl PCI Express Stromstecker 6+2pin	4
AC Eingangsspannung *	100 - 240 V	CPU Stecker (4+4 pin)	✓
AC Eingangsfrequenz	50 - 60 Hz	Kabeltyp	Nicht-modular
Eingangsstrom	8-4 A	Leistungen	
Leistungsfaktorkorrekturfilter (PFC)	Aktiv	80 Plus Zertifizierung *	80 PLUS Gold
Kombinierter Strom (+3.3V)	130 W	Zweck *	Server
Kombinierter Strom (+5V)	130 W	Stromversorgungseinheit (PSU)	PS/2
Max. Ausgangsstrom (+3.3V)	20 A	Formfaktor *	DBB
Max. Ausgangsstrom (+12V)	41,76 A	Design	
Max Ausgangsstrom (+5V)	20 A	Produktfarbe	Schwarz
Max. Ausgangsstrom (-12V)	0,5 A	Lüfterdurchmesser	4 cm
Max. Ausgangsstrom (+5Vsb)	3 A	Anzahl Lüfter	2 Lüfter
Effizienz	90%	Lieferumfang	
Energieschutzeigenschaften	Überstrom, Überlastung, Überspannung, Überhitzung, Kurzschluß, Unterspannung	Mitgelieferte Kabel	CPU, PCIe, SATA
Anschlüsse und Schnittstellen		Gewicht und Abmessungen	
Motherboard Anschlussstecker *	20+4 pin ATX	Breite	86 mm
Anzahl SATA Stromstecker	6	Tiefe	150 mm
Anzahl Molex Anschlüsse 4pin *	2	Höhe	190 mm
		Logistikdaten	
		Warentarifnummer (HS)	84733020



4713224523090

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 30-OCT-2026. Prints or copies of Information are only valid on the printed Publication date