FSP Clippers RT 2K Unterbrechungsfreie Stromversorgung (USV) Doppelwandler (Online) 2 kVA 2000 W



Marke : FSP

Artikel-Code: PPF20A0400

Produktname : Clippers RT 2K

FSP Clippers RT 2K. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 2 kVA, Ausgangsleistung: 2000 W. AC-Steckertypen: C13-Koppler, USB-Port-Typ: USB Typ-B, Serielle Schnittstelle: RS-232. Batteriekapazität: 9 Ah, Akku-/Batteriespannung: 12 V, Typische Backup-Zeit bei voller Belastung: 33 min. Formfaktor: Rackmount/Tower, Produktfarbe: Schwarz, Kühlung: Aktiv. Konformitätsbescheinigungen: CE, Zertifizierung: EMC EN62040-2 C2



Merkmale	
USV-Topologie *	Doppelwandler (Online)
Ausgangskapazität *	2 kVA
Ausgangsleistung *	2000 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	110 V
Eingangs-Betriebsspannung (max) *	300 V
Eingangsfrequenz *	40/70 Hz
Ausgangs-Betriebsspannung (min)	208 V
Ausgangs-Betriebsspannung (max)	240 V
Output Frequenz	46/64 Hz
Regulierung der Ausgangsspannung	1%
Reaktionszeit	4 ms
Anzahl der Eingangs-Phasen	1
Leistungsfaktor	0,99
Crest-Faktor	3:1
ECO-Modus	✔
Gesamtverzerrungsfaktor THD (lineare Last)	2%
Gesamtverzerrungsfaktor THD (nichtlineare Last)	4%
Geräuschpegel	50 dB
Druckanstiegsschutz	✔
Akustische Signale	✔
Akustische Alarm-Modi	Alarm bei Batteriebetrieb, Störung, Überlastungsalarm, Warnung bei geringer Batterie

Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler
USB Anschluss	✔
Anzahl USB 2.0 Anschlüsse	1
USB-Port-Typ	USB Typ-B

Anschlüsse und Schnittstellen	
Serielle Schnittstelle	✔
Serielle Schnittstelle	RS-232
Notaus-Steckverbinder (EPO)	✔

Akku/Batterie	
Batteriekapazität	9 Ah
Akku-/Batteriespannung	12 V
Anzahl Batteriezellen	4
Typische Backup-Zeit bei voller Belastung	33 min
Akkuladezeit	3 h
Hot-Swap-Batterie	✔

Design	
Formfaktor *	Rackmount/Tower
Kühlung	Aktiv
Eingebauter Ventilator	✔
Produktfarbe *	Schwarz
Steuerung	Tasten
Displaytyp	LCD

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	20 - 90%

Zertifikate	
Konformitätsbescheinigungen	CE
Zertifizierung	EMC EN62040-2 C2

Nachhaltigkeit	
Nachhaltigkeitskonformität	✔

Gewicht und Abmessungen	
Breite	438 mm
Tiefe	510 mm
Höhe	88 mm
Gewicht	19,5 kg

Logistikdaten	
Warentarifnummer (HS)	85078000

4713224524899

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 30-OCT-2026. Prints or copies of Information are only valid on the printed Publication date