

## TP-Link Omada EAP655-WALL(EU) WLAN Access Point 2402 Mbit/s Weiß Power over Ethernet (PoE)

**Marke :** TP-Link

**Produktfamilie:** Omada

**Artikel-Code:** EAP655-WALL(EU)

**Produktname :** EAP655-WALL(EU)

TP-Link Omada EAP655-WALL(EU). 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 2402 Mbit/s. Unterstützte Sicherheitsalgorithmen: HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA2-Enterprise, WPA3-Enterprise. Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß



| Merkmale                                 |                                                                                                                               | Anschlüsse und Schnittstellen            |                                                                                 |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------|
| 2,4 GHz *                                | ✓                                                                                                                             | Anzahl Ethernet-LAN-Anschlüsse (RJ-45) * | 4                                                                               |
| 5 GHz *                                  | ✓                                                                                                                             | WAN Port                                 | Ethernet (RJ-45)                                                                |
| 6 GHz *                                  | ✗                                                                                                                             | Gleichstrom-Anschluss (DC)               | ✓                                                                               |
| Maximale Datenübertragungsrate *         | 2402 Mbit/s                                                                                                                   | <b>Energie</b>                           |                                                                                 |
| Maximale Datenübertragungsrate (2,4 GHz) | 574 Mbit/s                                                                                                                    | Power over Ethernet (PoE) *              | ✓                                                                               |
| Maximale Datenübertragungsrate (5 GHz)   | 2402 Mbit/s                                                                                                                   | Stromverbrauch (Standardbetrieb)         | 12 W                                                                            |
| Ethernet LAN Datentransferraten          | 10,100,1000 Mbit/s                                                                                                            | <b>Design</b>                            |                                                                                 |
| Frequenzband                             | 2.4, 5 GHz                                                                                                                    | Platzierung *                            | Wand                                                                            |
| Netzstandard                             | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at | Produktfarbe *                           | Weiß                                                                            |
|                                          |                                                                                                                               | Kabelsperr-Slot                          | ✗                                                                               |
| Verkabelungstechnologie                  | 10/100/1000Base-T(X)                                                                                                          | Reset-Knopf                              | ✓                                                                               |
| Zahl der Benutzer                        | 100 Benutzer                                                                                                                  | LED-Anzeigen                             | ✓                                                                               |
| Automatische Kanalwahl                   | ✓                                                                                                                             | <b>Antenne</b>                           |                                                                                 |
| WLAN-Multimedia (WMM)/(WME)              | ✓                                                                                                                             | Antennentyp *                            | Intern                                                                          |
| VLAN-Unterstützung                       | ✓                                                                                                                             | Anzahl der Antennen                      | 2                                                                               |
| Ratenbeschränkung                        | ✓                                                                                                                             | Antenne Zunahmehöhe (max)                | 5 dBi                                                                           |
| Kabellose Isolierung                     | ✓                                                                                                                             | <b>Leistungen</b>                        |                                                                                 |
| Bandsteuerung                            | ✓                                                                                                                             | Kompatible Betriebssysteme               | Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows 11, Linux |
| Airtime Fairness (ATF)                   | ✓                                                                                                                             | <b>Zertifikate</b>                       |                                                                                 |
| Quality of Service (QoS) Support         | ✓                                                                                                                             | Konformitätsbescheinigungen              | RoHS                                                                            |
| BeamForming                              | ✓                                                                                                                             | Zertifizierung                           | FCC, RoHS                                                                       |
| Sendeleistung (CE)                       | 20 - 23 - 26 dbm                                                                                                              | <b>Gewicht und Abmessungen</b>           |                                                                                 |
| Sendeleistung (FCC)                      | 21 - 21 dbm                                                                                                                   | Breite                                   | 143 mm                                                                          |

| Sicherheit                                             |                                                                                    | Gewicht und Abmessungen              |             |
|--------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------|-------------|
| Unterstützte Sicherheitsalgorithmen *                  | HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA2-Enterprise, WPA3-Enterprise | Tiefe                                | 86 mm       |
| MAC Adressen Filtern                                   | ✓                                                                                  | Höhe                                 | 42,6 mm     |
| IP-Adressen Filter                                     | ✓                                                                                  | Verpackungsdaten                     |             |
| Funktionen Service Set Identifier (SSID)               | Multiple SSIDs                                                                     | Verpackungsbreite                    | 117 mm      |
| Anzahl der SSID-Unterstützung                          | 16                                                                                 | Verpackungstiefe                     | 184 mm      |
| Fernauthentifizierungs-Einwahl-Benutzerdienst (RADIUS) | ✓                                                                                  | Verpackungshöhe                      | 56 mm       |
| Zugriffkontrollliste                                   | ✓                                                                                  | Paketgewicht                         | 400 g       |
| Management-Funktionen                                  |                                                                                    | Verpackungsart                       | Box         |
| Web-basiertes Management                               | ✓                                                                                  | Lieferumfang                         |             |
| Syslog                                                 | ✓                                                                                  | Menge pro Packung                    | 1 Stück(e)  |
| Upgradefähige Firmware                                 | ✓                                                                                  | Montageset                           | ✓           |
|                                                        |                                                                                    | Betriebsbedingungen                  |             |
|                                                        |                                                                                    | Relative Luftfeuchtigkeit in Betrieb | 10 - 90%    |
|                                                        |                                                                                    | Betriebstemperatur                   | 0 - 40 °C   |
|                                                        |                                                                                    | Temperaturbereich bei Lagerung       | -40 - 70 °C |
|                                                        |                                                                                    | Luftfeuchtigkeit bei Lagerung        | 5 - 90%     |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.