



TP-Link Omada SG3218XP-M2 Managed L2+ 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) 1U Schwarz

Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: SG3218XP-M2(UN)



Produktname : SG3218XP-M2

TP-Link Omada SG3218XP-M2. Switch-Typ: Managed, Switch-Ebene: L2+. Basic Switching RJ-45 Ethernet Ports-Typ: 2.5G Ethernet (100/1000/2500), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 16, Konsolen-Port: RJ-45/Micro-USB. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 120 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1s, IEEE 802.1w. Netzstecker: AC-Eingangsbuchse. Power over Ethernet (PoE). Rack-Einbau, Formfaktor: 1U



Management-Funktionen		Sicherheit	
Switch-Typ *	Managed	IP-MAC-Portbindung	✓
Switch-Ebene	L2+	Authentifizierung	MAC-basierte Authentifizierung, Port-basierte Authentifizierung
Quality of Service (QoS) Support	✓	Passwortschutz	✓
Web-basiertes Management	✓	Autentifizierungstyp	AAA, TACACS+
Cloud-verwaltet	✓	Warteschleifenplanungs-Algorithmen	SP, WRR+SP, Weighted Round Robin (WRR)
ARP-Inspektion	✓		
Konfiguration der Standorteinstellungen (CLI)	✓	Multicast-Funktionen	
Systemereignisprotokoll	✓	Multicast Unterstützung	✓
MIB Unterstützung	MIB II (RFC1213), Interface MIB (RFC2233), Ethernet Interface MIB (RFC1643), Bridge MIB (RFC1493), P/Q-Bridge MIB (RFC2674), RMON MIB (RFC2819), RMON2 MIB (RFC2021), Radius Accounting Client MIB (RFC2620), Radius Authentication Client MIB (RFC2618), Remote Ping, Traceroute MIB (RFC2925), Support TP-Link private MIB	Multicast Listener Discovery (MLD) Snooping	✓
		Protokolle	
		Management-Protokolle	SNMP v1/v2c/v3, SNMP
		GARP VLAN Registration Protocol (GVRP)	✓
		Design	
		Rack-Einbau *	✓
		Formfaktor	1U
		Produktfarbe	Schwarz
		LED-Anzeigen	✓
		Anzahl Lüfter	2 Lüfter
		Energie	
		Energiequelle *	AC
		Netzteil enthalten *	✓
		AC Eingangsspannung	100 - 240 V
		AC Eingangsfrequenz	50/60 Hz
		Stromverbrauch (max.)	299,4 W

Netzwerk		Power over Ethernet (PoE)	
10G-Unterstützung *	✓	Power over Ethernet (PoE) *	✓
Port-Spiegelung	✓	Anzahl Power over Ethernet plus (PoE+) Anschlüsse	8
IP-Routing	✓	Power over Ethernet (PoE) Leistung pro Anschluss	30 W
Unterstützung Datenflusssteuerung	✓	Gesamtleistung Power over Ethernet (PoE)	240 W
Link Aggregation	✓	Betriebsbedingungen	
Broadcast-Sturmkontrolle	✓	Betriebstemperatur	0 - 50 °C
Ratenbeschränkung	✓	Temperaturbereich bei Lagerung	-40 - 70 °C
Spannbaum-Protokoll	✓	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Head-of-Line (HOL)-Blocking	✓	Luftfeuchtigkeit bei Lagerung	5 - 90%
Ethernet LAN Datentransferraten	100,1000,2500 Mbit/s	Wärmeableitung	1021,64 BTU/h
VLAN-Unterstützung	✓	Gewicht und Abmessungen	
Virtuelle LAN-Funktionen	MAC address-based VLAN, Port-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN	Breite	440 mm
		Tiefe	180 mm
		Höhe	44 mm
		Datenübertragung	
Routing-/Switching-Kapazität *	120 Gbit/s	Lieferumfang	
Transferrate	89,28 Mpps	Mitgelieferte Kabel	AC
MAC-Adressentabelle *	16000 Eintragungen	Schnellstartübersicht	✓
Statische Route	✓	Verpackungsdaten	
Anzahl der statischen Routen	48	Verpackungsart	Box
Anzahl IP-Schnittstellen	32	Nachhaltigkeit	
Jumbo Frames Unterstützung	✓	Nachhaltigkeitskonformität	✓
Jumbo-Frames	9000	Zertifikate	
Datenpaket-Pufferspeicher	12 MB	Konformitätsbescheinigungen	Eidgenössische Kommunikationskommission (FCC), RoHS
Sicherheit		Zertifizierung	CE, FCC, RoHS
DHCP-Funktionen	DHCP client, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping		
Zugriffkontrollliste	✓		
IGMP-Snooping	✓		
Unterstützte Sicherheitsalgorithmen	HTTPS, SSH, SSH-2, SSL/TLS		
MAC Adressen Filtern	✓		
Statische Anschlusssicherheit	✓		
SSH-/SSL-Unterstützung	✓		
Loop Protection	✓		
BPDU-Filterung/Schutz	✓		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.